



Food Grade Penetrating Oil, 11 Wt Oz No. 03086 | Item# 1003355 | Case# 1003354

Product Description

on food processing equipment. It penetrates and loosens rust, scale, corrosion and dirt to free corroded parts and fasteners. Contains no silicones.
Food processing equipment exposed to food products including scales, fans, carts, galleys, bottlers, chutes, conveyors, racks, ovens, stoves, fillers, mixers, freezers, rails and cooking appliances.
16 Ounce Aerosol
CRC
General Purpose Lubricant For Food Processing Equipment with $\mbox{Perma-Lock}{}^{\mbox{\ensuremath{\mathbb{R}}}}$
11 Wt Oz
078254030869
7.75H x 2.63W x 2.63D in
12
8.1H x 8.3W x 11.1D in
133
13 lbs
30078254030860
Clear Colorless Liquid
Mineral Oil
200°F
93°C
None
0.82
Safe on Most Plastics (Test small area)
Thin, Oily, Non-Drying
Very Slow
Not Determined

An effective and efficient general purpose lubricant for use

Last revised: 1/21/2021

Page 1 of 2





CR@

Working Temp (F)	32 to 300°F
Working Temp (C)	0 to 148.9°C
Propellant	Carbon Dioxide
NSF Category Code	H1
NSF Number	130546
Aerosol Flammability Level	Ш
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Penetrant
Removal (How To)	Remove with Petroleum Distillates.



Page 2 of 2







Food Grade Penetrating Oil, 11 Wt Oz No. 03086 | Item# 1003355 | Case# 1003354

Product Description

on food processing equipment. It penetrates and loosens rust, scale, corrosion and dirt to free corroded parts and fasteners. Contains no silicones.
Food processing equipment exposed to food products including scales, fans, carts, galleys, bottlers, chutes, conveyors, racks, ovens, stoves, fillers, mixers, freezers, rails and cooking appliances.
16 Ounce Aerosol
CRC
General Purpose Lubricant For Food Processing Equipment with $\mbox{Perma-Lock}{}^{\mbox{\ensuremath{\mathbb{R}}}}$
11 Wt Oz
078254030869
7.75H x 2.63W x 2.63D in
12
8.1H x 8.3W x 11.1D in
133
13 lbs
30078254030860
Clear Colorless Liquid
Mineral Oil
200°F
93°C
None
0.82
Safe on Most Plastics (Test small area)
Thin, Oily, Non-Drying
Very Slow
Not Determined

An effective and efficient general purpose lubricant for use

Last revised: 1/21/2021

Page 1 of 2





CR@

Working Temp (F)	32 to 300°F
Working Temp (C)	0 to 148.9°C
Propellant	Carbon Dioxide
NSF Category Code	H1
NSF Number	130546
Aerosol Flammability Level	Ш
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Penetrant
Removal (How To)	Remove with Petroleum Distillates.



Page 2 of 2

