

F

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## 05400742920 Splice Kit U1 STD, 1.8" Conn, 8" Tube

Minnesota Mining (3M)	
Catalog Number	05400742920
Manufacturer	Minnesota Mining (3M)
Description	3M™ Scotchlok™ Uf Series Standard Splice Kits Include All The
	Accessories Required to Offer A Reliable, Moisture Proof
	Electrical Connection For Type Uf B Underground Feeders. These
	Kits Are Suitable to Use On 600V Rated, Flat, Non Shielded Uf
	Cables.
Weight per unit	0.2050 (lbs/each)
Product Category	Splicing & Terminating Kits
Descriptions	
Description	SPLICE KIT UF1 STANDARD,6/CASE
extra long description	3M 7000132746 3M™ Splice Kit UF
Features	The Splice Kit UF Series consists of a connector insulation
	assembly and a heat shrink tube. The connector assembly
	contains four cylindrical set screw connectors separated by a
	piece of vinyl insulation. The heat shrink tube is a heavy wall,
	adhesive lined tube and is UL Listed and RoHS 2011/65/EU
	Compliant. It withstands a temperature range of 67 to 230
	degrees F ( 55 to 110 degrees C).
Long Description	3M™ Scotchlok™ UF Series Standard Splice Kits include all the
	accessories required to offer a reliable, moisture proof electrical
	connection for type UF B underground feeders. These kits are
	suitable to use on 600V rated, flat, non shielded UF cables.
Product Type	3M™ Splice Kit Uf
Manufacturer Information	
Brand	3M
GTIN	00054007429203
Manufacturers Part Number	7000132746
UPC	054007429203
axonomies, Classifications, and Cat	tegories
Category Description	SPLICE KITS
Туре	Splice Kit
Packaging	
Carton	1
Weight Per each	0.205
<b>v</b>	र । <del>ज</del> ्म स
Jses, Certifications, and Standards	type LLE Dunderground feeder coble rated for 600 yelts (Conne
Application	type U.FB underground feeder cable rated for 600 volts (Coppe Wire Only) ranging from $#14/3$ without ground wire up to $#8/3$
	Wire Only) ranging from #14/3 without ground wire up to #8/3 with ground wire
	with ground wire