



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



OT4 1 1/4 AL T Conduit Body

Hubbell--Killark

| | |
|------------------|--|
| Catalog Number | OT4 |
| Manufacturer | Hubbell--Killark |
| Description | O Series/Duraloy 5 Series - Aluminum Conduit Body - T Type - Hub SIZE1-1/4 Inch - Volume 32.0 Cubic Inches |
| Weight per unit | 1.6 (lbs/each) |
| Product Category | Alum |

Material, Color, and Finish

| | |
|--------|--|
| Color | Gray;Grey |
| Finish | Electrostatically applied powder coating |

Dimensions and Weight

| | |
|----------|--------|
| Height | 2-5/8 |
| Hub Size | 1-1/4" |
| Length | 9-3/16 |
| Width | 3-1/2 |

Descriptions

| | |
|------------------------|--|
| Description | 1 1/4 AL T CONDUIT BODY |
| extra long description | KLRK OT-4 1-1/4" "T" TYPE AL COND |
| Long Description | O SERIES/DURALOY 5 SERIES - ALUMINUM CONDUIT BODY - T TYPE - HUB SIZE1-1/4 INCH - VOLUME 32.0 CUBIC INCHES |
| Product Type | 1-1/4" "T" Type Al Conduit B |
| Special Features | Tapered threaded hubs (NPT). Raintight when used with gasketed covers. Interchangeable with competitive products. Volume is 32 cu. in. |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | KILLARK |
| GTIN | 00783936530048 |
| Manufacturers Part Number | OT-4 |
| UPC | 783936530048 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------------|
| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS |
| Type | Aluminum conduit body |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 1.55 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

standard

UL, CSA