

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### 101048HSNK Wway 10X10X48 N1 HC

101048HSNK
Cooper B-Line/Cable Tray
Eaton B-Line Series Wireway, 10" Height, 48" Length, 10" Width, HSNK Wireway, Thru Holes, No Knockouts, Hinged Cover, Nema 1, Steel, Hinged, Ansi 61 Gray, 14 Gauge
34.7 (lbs/each)
Nema Type 1 Wireway & Fittings
HINGED
48.0000 IN X 10.0000 IN X 10.0000 IN
14 GAUGE STEEL
48 In
Gray
10.00 ln
48.00 in
10.00 ln
WWAY 10X10X48 N1 HC
B-LINE 101048 HSNK HINGE SCREW CVR
Eaton's B-Line series wiring troughs provide reliable
environmental protection and are used to house runs of control and power cable in wiring, junction, pull, and termination
applications.
Eaton B-Line series wireway, 10" height, 48" length, 10" width,
HSNK wireway, Thru holes, No knockouts, Hinged cover, NEMA 1
Steel, Hinged, ANSI 61 gray, 14 gauge
Hinge Screw CVR Wireway, No Knockouts, 10X10X48
Eaton
00782051479287

#### Ma

Brand	Eaton
GTIN	00782051479287
Manufacturers Part Number	101048HSNK
UPC	782051479287

### **Taxonomies, Classifications, and Categories**

Category Description	STEEL WIRE WAY JUNCTION BOXES
Туре	Wireway



standard

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	34.71
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Power Distribution and ControlsInd Facilities & Factories - Facility: Safety and Security SystemsInd Facilities & Factories - Facility: Power Distribution and ControlInd Facilities & Factories - Facility: Lighting and Lighting ControlsInd Facilities & Factories - Facility: Critical PowerInd Facilities & Factories - Industrial Facilities/Factories - OtherCommercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures -
Enclosure	NEMA 1, IP30

UL Listed, CSA C22.2.