



## HT50 HIGH TENSION HACKSAW 50,000 PSI

### HIGHEST TENSION. EVER

Unique I-beam construction allows blade to tension up to 50,000 psi, resulting in fast, straight cuts

### COMFORTABLE GRIPS

Rubberized handles allow for confident handling even in wet or cold environments

### CONVERT TO A JAB SAW

Accepts any LENOX reciprocating saw blade to be used as a jab saw

### CONVENIENT BLADE STORAGE

Store up to 5 extra 12" hacksaw blades in the I-Beam



PROD NO	BLADE SPECIFICATION
12132HT50	12" (300mm) 24TPI Hacksaw Blade



Tension



Use as a Jab Saw



Stores up to 5 Blades



Comfort Grips

## 5012 LOW PROFILE HACKSAW 40,000 PSI

### HIGH TENSION

Allows blade to tension up to 40,000 PSI, resulting in fast, straight cuts

### FITS INTO TIGHT SPOTS

Low profile tip easily handles close-quarter cuts

### MULTI-PURPOSE

Mount blade at 45 degrees for flush cutting applications

PROD NO	BLADE SPECIFICATION
209205012	12" (300mm) 24TPI Hacksaw Blade



Flush Cutting



## HT50 HIGH TENSION HACKSAW 50,000 PSI

### HIGHEST TENSION. EVER

Unique I-beam construction allows blade to tension up to 50,000 psi, resulting in fast, straight cuts

### COMFORTABLE GRIPS

Rubberized handles allow for confident handling even in wet or cold environments

### CONVERT TO A JAB SAW

Accepts any LENOX reciprocating saw blade to be used as a jab saw

### CONVENIENT BLADE STORAGE

Store up to 5 extra 12" hacksaw blades in the I-Beam



PROD NO	BLADE SPECIFICATION
12132HT50	12" (300mm) 24TPI Hacksaw Blade



Tension



Use as a Jab Saw



Stores up to 5  
Blades



Comfort Grips

## 5012 LOW PROFILE HACKSAW 40,000 PSI

### HIGH TENSION

Allows blade to tension up to 40,000 PSI, resulting in fast, straight cuts

### FITS INTO TIGHT SPOTS

Low profile tip easily handles close-quarter cuts

### MULTI-PURPOSE

Mount blade at 45 degrees for flush cutting applications

PROD NO	BLADE SPECIFICATION
209205012	12" (300mm) 24TPI Hacksaw Blade



Flush Cutting