

LED CORDLIGHT

Engineered Products Company's (EPCO) LED CordLights are an energy efficient, labor saving alternative to traditional string lights. Constructed of heavy-duty 18/2 SJTW round cord and available in 50- or 100-foot lengths, these CordLights are ETL Listed, comply with UL Standard 153 for Portable Electric Luminaires, and are suitable for a variety of temporary construction lighting applications.

BENEFITS

- Each LED Module produces excellent 5000K white light.
- Labor savings! Easy installation and no lamps to replace.
- Reduced energy costs with minimal power draw.
- Tested for optimal performance, durability, and reliability.
- Suitable for damp and wet locations.
- IP65 Weather-resistant LED Modules resist dust and rain.
- Beam Angle: 120°.
- Linkable to connect additional LED CordLights up to 500-feet.

FEATURES

- Commercial grade, high-power LEDs.
- Available in 50- or 100-foot lengths.
- 10-foot spacing between LED Modules.
- Constructed of heavy-duty 18/2 SJTW round cord.
- 120-Volt plug and receptacle.
- Includes carabiner coupling link to expedite installation.

TYPICAL APPLICATIONS

- | | |
|-------------------------------|----------------------------|
| ▪ Construction Sites | ▪ Special Events |
| ▪ Parking Lots | ▪ Christmas Tree Lots |
| ▪ Walkways | ▪ Outdoor Markets |
| ▪ Bar and Restaurant Lighting | ▪ Commercial |
| ▪ Festivals | ▪ Patio and Outdoor Spaces |
| ▪ Circus Tents | ▪ Home Décor Lighting |



LED CORDLIGHT



Carabiner Coupling Link



120-Volt Plug and Receptacle

LED CORDLIGHTS

| LED CORDLIGHTS SPECIFICATIONS | | |
|------------------------------------|---|---|
| | 16040 — 100-Foot Length | 16045 — 50-Foot Length |
| Output Lumens | 10,000 (1,000 per LED Light Module) | 5,000 (1,000 per LED Light Module) |
| Operating Voltage | 120 VAC @ 60/50 Hz | 120 VAC @ 60/50 Hz |
| Power Consumption | 80-Watts | 40-Watts |
| Correlated Color Temperature (CCT) | 5000K | 5000K |
| Color Rendering Index (CRI) | ≥80 | ≥80 |
| Efficacy | 125 lm/W | 125 lm/W |
| Ambient Operating Temperature | -4°F (-20°C) to 104°F (40°C) | -4°F (-20°C) to 104°F (40°C) |
| Environment | Damp or Wet Locations | Damp or Wet Locations |
| Certifications | <ul style="list-style-type: none"> Complies with UL Standard 153 for Portable Electric Luminaires ETL Listed. Product Compliant to North American Safety Standards Meets all OSHA Standards Meets the requirements of the 2020 National Electrical Code | <ul style="list-style-type: none"> Complies with UL Standard 153 for Portable Electric Luminaires ETL Listed. Product Compliant to North American Safety Standards Meets all OSHA Standards Meets the requirements of the 2020 National Electrical Code |
| Power Cord Type | <ul style="list-style-type: none"> 18/2 Heavy Duty SJTW Cord 120V Plug and Receptacle | <ul style="list-style-type: none"> 18/2 Heavy Duty SJTW Cord 120V Plug and Receptacle |
| LED Module/Power Cord Color | Black/Yellow | Black/Yellow |
| Warranty | 1 Year | 1 Year |
| Linkable Maximum | Five (5) Maximum | Ten (10) Maximum |

Replacement Fuse: Bussman Series — Product Code: GMA8-R

| Catalog Number | UPC Number | Description | Order Unit | Unit Qty | Unit Pkg | Units/Case | TL Case Qty | Min Order Qty | MM Req | Ship Wt (Lbs) |
|----------------|------------|-------------------------------|------------|----------|----------|------------|-------------|---------------|--------|---------------|
| 16040 | 16040 | LED CordLights: 100-FT Length | EA | 1 | BX | 2 | 2 | 1 | No | 20 |
| 16045 | 16045 | LED CordLights: 50-FT Length | EA | 1 | BX | 4 | 4 | 1 | No | 20 |

Distributed By:



UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BRL (Barrel); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

E02-150-042 A1 (10/19-BB)
©2019 Engineered Products Company. All Rights Reserved.

www.engproducts.com

5401 SMETANA DRIVE | MINNETONKA, MN 55343
P 800.336.1976 | F 800.336.2801

Specifications subject to change without prior notice.



**ENGINEERED
PRODUCTS CO.**

LED CORDLIGHT

Engineered Products Company's (EPCO) LED CordLights are an energy efficient, labor saving alternative to traditional string lights. Constructed of heavy-duty 18/2 SJTW round cord and available in 50- or 100-foot lengths, these CordLights are ETL Listed, comply with UL Standard 153 for Portable Electric Luminaires, and are suitable for a variety of temporary construction lighting applications.

BENEFITS

- Each LED Module produces excellent 5000K white light.
- Labor savings! Easy installation and no lamps to replace.
- Reduced energy costs with minimal power draw.
- Tested for optimal performance, durability, and reliability.
- Suitable for damp and wet locations.
- IP65 Weather-resistant LED Modules resist dust and rain.
- Beam Angle: 120°.
- Linkable to connect additional LED CordLights up to 500-feet.

FEATURES

- Commercial grade, high-power LEDs.
- Available in 50- or 100-foot lengths.
- 10-foot spacing between LED Modules.
- Constructed of heavy-duty 18/2 SJTW round cord.
- 120-Volt plug and receptacle.
- Includes carabiner coupling link to expedite installation.

TYPICAL APPLICATIONS

- | | |
|-------------------------------|----------------------------|
| ▪ Construction Sites | ▪ Special Events |
| ▪ Parking Lots | ▪ Christmas Tree Lots |
| ▪ Walkways | ▪ Outdoor Markets |
| ▪ Bar and Restaurant Lighting | ▪ Commercial |
| ▪ Festivals | ▪ Patio and Outdoor Spaces |
| ▪ Circus Tents | ▪ Home Décor Lighting |



LED CORDLIGHT



Carabiner Coupling Link



120-Volt Plug and Receptacle

LED CORDLIGHTS

| LED CORDLIGHTS SPECIFICATIONS | | |
|------------------------------------|---|---|
| | 16040 — 100-Foot Length | 16045 — 50-Foot Length |
| Output Lumens | 10,000 (1,000 per LED Light Module) | 5,000 (1,000 per LED Light Module) |
| Operating Voltage | 120 VAC @ 60/50 Hz | 120 VAC @ 60/50 Hz |
| Power Consumption | 80-Watts | 40-Watts |
| Correlated Color Temperature (CCT) | 5000K | 5000K |
| Color Rendering Index (CRI) | ≥80 | ≥80 |
| Efficacy | 125 lm/W | 125 lm/W |
| Ambient Operating Temperature | -4°F (-20°C) to 104°F (40°C) | -4°F (-20°C) to 104°F (40°C) |
| Environment | Damp or Wet Locations | Damp or Wet Locations |
| Certifications | <ul style="list-style-type: none"> Complies with UL Standard 153 for Portable Electric Luminaires ETL Listed. Product Compliant to North American Safety Standards Meets all OSHA Standards Meets the requirements of the 2020 National Electrical Code | <ul style="list-style-type: none"> Complies with UL Standard 153 for Portable Electric Luminaires ETL Listed. Product Compliant to North American Safety Standards Meets all OSHA Standards Meets the requirements of the 2020 National Electrical Code |
| Power Cord Type | <ul style="list-style-type: none"> 18/2 Heavy Duty SJTW Cord 120V Plug and Receptacle | <ul style="list-style-type: none"> 18/2 Heavy Duty SJTW Cord 120V Plug and Receptacle |
| LED Module/Power Cord Color | Black/Yellow | Black/Yellow |
| Warranty | 1 Year | 1 Year |
| Linkable Maximum | Five (5) Maximum | Ten (10) Maximum |

Replacement Fuse: Bussman Series — Product Code: GMA8-R

| Catalog Number | UPC Number | Description | Order Unit | Unit Qty | Unit Pkg | Units/Case | TL Case Qty | Min Order Qty | MM Req | Ship Wt (Lbs) |
|----------------|------------|-------------------------------|------------|----------|----------|------------|-------------|---------------|--------|---------------|
| 16040 | 16040 | LED CordLights: 100-FT Length | EA | 1 | BX | 2 | 2 | 1 | No | 20 |
| 16045 | 16045 | LED CordLights: 50-FT Length | EA | 1 | BX | 4 | 4 | 1 | No | 20 |

Distributed By:



UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BRL (Barrel); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton

E02-150-042 A1 (10/19-BB)
©2019 Engineered Products Company. All Rights Reserved.

www.engproducts.com

5401 SMETANA DRIVE | MINNETONKA, MN 55343
P 800.336.1976 | F 800.336.2801

Specifications subject to change without prior notice.



**ENGINEERED
PRODUCTS CO.**