

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



18132C Ub Gel Filled Splicing Connectors 22-26 Awg *Nsi Industries*

Catalog Number	18132C
Manufacturer	Nsi Industries
Description	Platinum 18132C Ub Gelfilled Connec
Weight per unit	0.2000 (lbs/each)
Product Category	Boxes & Covers
Descriptions	
Description	UB GEL FILLED SPLICING CONNECTORS 22-26 AWG
Features	The Telcom Splicing Connectors utilize an insulation
	displacement contact design for fast, simple, reliable
	terminations. No wire stripping is required and connectors will accept wire of different gauges. All connectors are Gel filled to
	provide moisture resistance and inhibit corrosion. For use with
	solid copper conductors only. Typical uses include Butt Splicing 2
	or 3 wires of the same or different gauges. Perfect for pigtail and
	load coil splice applications. Use the UB connector for tapping
	onto an ex
Long Description	PLATINUM 18132C UB GelFilled Connec
Product Type	Ub Gelfilled Connector 22-26 Awg 100/CLM
Special Features	26-22 AWG, in-line tap; Max insulation OD, .050" (1.27mm).; Tap
-	directly on to existing wire without interrupting service
Manufacturor Information	

Manufacturer Information

Brand	Platinum Tools
GTIN	00849160006824
Manufacturers Part Number	18132C
UPC	849160006824

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Connectors

Availability

Manufacturer Status	Inactive
---------------------	----------

Packaging

Carton	1
Package	4
Weight Per each	0.2

Uses, Certifications, and Standards

ŀ	Application	Cable Installation
---	-------------	--------------------