

PHOTOCONTROLS

1/2" Conduit Mount

180° Swivel, Lexan® Housing

2001 Series



SPECIFICATIONS

- **ON/OFF:** Turn ON is 1 to 5fc, Turn OFF is 3 to 15fc, without the slide in position. ON/OFF adjustment is easily made by moving a slide cover. No tools required.
- **Time Delay:** ON and OFF.
- **Cell:** Cadmium sulphide, epoxy conformal coated 1/2" diameter.
- **Contacts:** Remain closed between dusk and dawn. (The unit fails in the ON position).
- **Lead Wires:** Three color coded, minimum 6" wire leads, #16AWG, rated for 105 °C.
- **Power Consumption:** Averages under 1 watt.
- **Temperature Range:** -40 °F to +140 °F (-40 °C to +60 °C).
- **Fail Mode:** ON.
- **Warranty:** 5 years.

APPLICATIONS

- Flood Lamp.
- Patio Lamp.
- Decorative lighting.

FEATURES

- **Sensor:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.
- **Operation:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.
- **Standards:** Meets ANSI/UL773A.
- **Housing:** All Lexan® enclosures are impact and vandal resistant. Translucent Lexan® Dome prolongs cell life by further screening out ultraviolet rays. Dome and base are ultrasonically welded for maximum strength.
- **Energy Savings:** Works with screw base CFLs.

ACCESSORIES

- **73866:** See page 434.

ACCESSORY

73866



| CAT. NO. | CERTIFICATION | UPC CODE | VOLTAGE VAC 50/60Hz | RATING | | |
|----------|---------------|----------|------------------------|------------|-------------|-------------|
| | | | | TUNGSTEN | BALLAST | LED |
| 2001 | cULus | 60015 | 120 | 2000W | 1800VA | 600VA |
| 2002 | cULus | 60016 | 208-277 | 3470-4620W | 2080-2770VA | 1040-1385VA |
| 2006 | CSA | 60028 | 347 | 5760W | 3470VA | — |
| 2018 | — | 62021 | 480 | 7500W | 4800VA | — |

PHOTOCONTROLS

1/2" Conduit Mount

180° Swivel, Lexan® Housing

2001 Series



SPECIFICATIONS

- **ON/OFF:** Turn ON is 1 to 5fc, Turn OFF is 3 to 15fc, without the slide in position. ON/OFF adjustment is easily made by moving a slide cover. No tools required.
- **Time Delay:** ON and OFF.
- **Cell:** Cadmium sulphide, epoxy conformal coated 1/2" diameter.
- **Contacts:** Remain closed between dusk and dawn. (The unit fails in the ON position).
- **Lead Wires:** Three color coded, minimum 6" wire leads, #16AWG, rated for 105 °C.
- **Power Consumption:** Averages under 1 watt.
- **Temperature Range:** -40 °F to +140 °F (-40 °C to +60 °C).
- **Fail Mode:** ON.
- **Warranty:** 5 years.

APPLICATIONS

- Flood Lamp.
- Patio Lamp.
- Decorative lighting.

FEATURES

- **Sensor:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.
- **Operation:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.
- **Standards:** Meets ANSI/UL773A.
- **Housing:** All Lexan® enclosures are impact and vandal resistant. Translucent Lexan® Dome prolongs cell life by further screening out ultraviolet rays. Dome and base are ultrasonically welded for maximum strength.
- **Energy Savings:** Works with screw base CFLs.

ACCESSORIES

- **73866:** See page 434.

ACCESSORY

73866



| CAT. NO. | CERTIFICATION | UPC CODE | VOLTAGE VAC 50/60Hz | RATING | | |
|----------|---------------|----------|------------------------|------------|-------------|-------------|
| | | | | TUNGSTEN | BALLAST | LED |
| 2001 | cULus | 60015 | 120 | 2000W | 1800VA | 600VA |
| 2002 | cULus | 60016 | 208-277 | 3470-4620W | 2080-2770VA | 1040-1385VA |
| 2006 | CSA | 60028 | 347 | 5760W | 3470VA | — |
| 2018 | — | 62021 | 480 | 7500W | 4800VA | — |