



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



2054 Rac Conduit Hanger 1 In RGD/Emt (TS 2)

Hubbell--Raco

| | |
|------------------|--|
| Catalog Number | 2054 |
| Manufacturer | Hubbell--Raco |
| Description | Conduit Hangers With Nut and Bolt, Steel, 2 Trade Size, 1 In. Rigid&Imc Size, 1 In. Emt Size |
| Weight per unit | 0.1190 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|-----------------|-------|
| Material | Steel |
| pallet quantity | 10000 |

Material, Color, and Finish

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Dimensions and Weight

| | |
|------|--------------------------------|
| Size | 2.438 in x 0.875 in x 1.203 in |
|------|--------------------------------|

Descriptions

| | |
|------------------------|--|
| Construction | One piece hanger with nut and bolt |
| Description | RAC CONDUIT HANGER 1 IN RGD/EMT (TS 2) |
| extra long description | RACO 2054 CONDUIT HANGER 1 IN RGD/E |
| Long Description | Conduit Hangers with Nut and Bolt, Steel, 2 Trade Size, 1 In. Rigid&IMC Size, 1 In. EMT Size |
| Product Type | Conduit Hanger 1 In RGD/Emt (TS 2) |
| Special Features | wet or dry locations, pregalvanized finish provides corrosion protection |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | RACO |
| GTIN | 00050169020548 |
| Manufacturers Part Number | 2054 |
| UPC | 050169020548 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS |
| Type | Rigid/IMC and EMT conduit |

Packaging

| | |
|-----------------|-------|
| Carton | 1 |
| Weight Per each | 0.119 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

For use in wet or dry locations to support runs of rigid/IMC and EMT conduit from ceilings and walls

standard

UL 514B