

BI-METAL RECIP BLADES

Cuts Stronger, Faster and Lasts Longer



THE LENOX® ADVANTAGE™

- **Shatter resistant**
Bi-metal blades bend and resist breaking and extend blade life.
- **Designed to attack**
Unique blade geometry positions the blade for optimum cutting performance.
- **Long lasting**
TUFFTOOTH™ design is reinforced to cut stronger and last longer.



Blade Specifications

| TPI | Length (Inches) | Product Number 5/pack | Product Number 25/pack | Product Number 1/pack | Width (Inches) | Thickness (Inches) | Applications |
|-------|-----------------|-----------------------|------------------------|-----------------------|----------------|--------------------|--|
| 4 | 6 | 20575-634R | — | 20574-S634R | 3/4 | .050 | Extra fast cutting in thick, nail-free wood |
| 6 | 4 | 20449-456RP | — | 20501-S456RP | 3/4 | .050 | For plaster, plaster board & lath. Bi-directional cutting |
| 6 | 6 | 20570-636RP | 20497-B636RP | 20571-S636RP | 3/4 | .050 | |
| 6 | 6 | 20560-606R | 20492-B606R | 20559-S606R | 3/4 | .035 | Fast cutting for wood, composition materials, plastics & non-ferrous metal |
| 6 | 6 | 20556-676RC | — | 20557-S676RC | 7/16 | .050 | Contour cutting in all woods, nail-embedded wood & composition materials |
| 6 | 6 | 20572-656R | 20530-B656R | 20573-S656R | 3/4 | .050 | Fast cutting. Roughing-in work & nail-embedded wood |
| 6 | 9 | 20582-956R | 20558-B956R | 20587-S956R | 3/4 | .050 | |
| 6 | 12 | 20585-156R | 20495-B156R | 20586-S156R | 3/4 | .050 | |
| 10 | 6 | 20562-610R | 20493-B610R | 20561-S610R | 3/4 | .035 | Nail-embedded wood, Composition materials & plastics. Pipe, Carbon steel, Stainless steel: 1/8"–1/4". Non-ferrous metal: 1/8"–1/2" thick |
| 10 | 8 | 20580-810R | 20590-B810R | 20581-S810R | 3/4 | .050 | |
| 10/14 | 8 | 20577-850R | 20535-B850R | 20588-S850R | 3/4 | .050 | Wood, Nail-embedded wood, Pipe, Carbon steel, Stainless steel: 1/8"–1/4"; Non-ferrous metal: 1/8"–1/2" thick, Demolition work, Fire & rescue |
| 10/14 | 12 | 20583-110R | 20491-B110R | 20584-S110R | 3/4 | .050 | |
| 14 | 3-5/8 | 20520-314RC | — | 20519-S314RC | 5/16 | .035 | Contour cutting in wood < 3/4" thick & in metal 3/32"–5/16" thick. |
| 14 | 4 | 20550-414R | 20488-B414R | 20551-S414R | 3/4 | .035 | Pipe, Structural steel, Stainless steel: 3/32"–1/4"; Non-ferrous metal: 3/32"–3/8" |
| 14 | 6 | 20564-614R | 20494-B614R | 20565-S614R | 3/4 | .035 | |
| 14 | 8 | 21519-814R | — | — | 3/4 | .035 | |
| 18 | 3-5/8 | 20521-318RC | — | 20522-S318RC | 5/16 | .035 | Contour cutting in metal: 1/16"–1/8" |
| 18 | 4 | 20552-418R | 20489-B418R | 20553-S418R | 3/4 | .035 | Structural steel, Pipe, Conduit, Stainless steel: 1/16"–3/16" thick, Non-ferrous metal: 1/16"–5/16" |
| 18 | 6 | 20566-618R | 20529-B618R | 20567-S618R | 3/4 | .035 | |
| 18 | 8 | 20578-818R | 20487-B818R | 20563-S818R | 3/4 | .035 | |
| 18 | 12 | 21510-118R | 21511-B118R | — | 3/4 | .035 | |
| 24 | 4 | 20554-424R | 20490-B424R | 20555-S424R | 3/4 | .035 | |
| 24 | 6 | 20568-624R | 20496-B624R | 20569-S624R | 3/4 | .035 | |
| 24 | 8 | 20579-824R | — | — | 3/4 | .035 | All metals less than 1/8" thick, Tubing, Conduit, Trim |

BI-METAL RECIP BLADES

Cuts Stronger, Faster and Lasts Longer



THE LENOX® ADVANTAGE™

- **Shatter resistant**
Bi-metal blades bend and resist breaking and extend blade life.
- **Designed to attack**
Unique blade geometry positions the blade for optimum cutting performance.
- **Long lasting**
TUFFTOOTH™ design is reinforced to cut stronger and last longer.



Blade Specifications

| TPI | Length (Inches) | Product Number 5/pack | Product Number 25/pack | Product Number 1/pack | Width (Inches) | Thickness (Inches) | Applications |
|-------|-----------------|-----------------------|------------------------|-----------------------|----------------|--------------------|--|
| 4 | 6 | 20575-634R | — | 20574-S634R | 3/4 | .050 | Extra fast cutting in thick, nail-free wood |
| 6 | 4 | 20449-456RP | — | 20501-S456RP | 3/4 | .050 | For plaster, plaster board & lath. Bi-directional cutting |
| 6 | 6 | 20570-636RP | 20497-B636RP | 20571-S636RP | 3/4 | .050 | |
| 6 | 6 | 20560-606R | 20492-B606R | 20559-S606R | 3/4 | .035 | Fast cutting for wood, composition materials, plastics & non-ferrous metal |
| 6 | 6 | 20556-676RC | — | 20557-S676RC | 7/16 | .050 | Contour cutting in all woods, nail-embedded wood & composition materials |
| 6 | 6 | 20572-656R | 20530-B656R | 20573-S656R | 3/4 | .050 | Fast cutting. Roughing-in work & nail-embedded wood |
| 6 | 9 | 20582-956R | 20558-B956R | 20587-S956R | 3/4 | .050 | |
| 6 | 12 | 20585-156R | 20495-B156R | 20586-S156R | 3/4 | .050 | |
| 10 | 6 | 20562-610R | 20493-B610R | 20561-S610R | 3/4 | .035 | Nail-embedded wood, Composition materials & plastics. Pipe, Carbon steel, Stainless steel: 1/8"–1/4". Non-ferrous metal: 1/8"–1/2" thick |
| 10 | 8 | 20580-810R | 20590-B810R | 20581-S810R | 3/4 | .050 | |
| 10/14 | 8 | 20577-850R | 20535-B850R | 20588-S850R | 3/4 | .050 | Wood, Nail-embedded wood, Pipe, Carbon steel, Stainless steel: 1/8"–1/4"; Non-ferrous metal: 1/8"–1/2" thick, Demolition work, Fire & rescue |
| 10/14 | 12 | 20583-110R | 20491-B110R | 20584-S110R | 3/4 | .050 | |
| 14 | 3-5/8 | 20520-314RC | — | 20519-S314RC | 5/16 | .035 | Contour cutting in wood < 3/4" thick & in metal 3/32"–5/16" thick. |
| 14 | 4 | 20550-414R | 20488-B414R | 20551-S414R | 3/4 | .035 | Pipe, Structural steel, Stainless steel: 3/32"–1/4"; Non-ferrous metal: 3/32"–3/8" |
| 14 | 6 | 20564-614R | 20494-B614R | 20565-S614R | 3/4 | .035 | |
| 14 | 8 | 21519-814R | — | — | 3/4 | .035 | |
| 18 | 3-5/8 | 20521-318RC | — | 20522-S318RC | 5/16 | .035 | Contour cutting in metal: 1/16"–1/8" |
| 18 | 4 | 20552-418R | 20489-B418R | 20553-S418R | 3/4 | .035 | Structural steel, Pipe, Conduit, Stainless steel: 1/16"–3/16" thick, Non-ferrous metal: 1/16"–5/16" |
| 18 | 6 | 20566-618R | 20529-B618R | 20567-S618R | 3/4 | .035 | |
| 18 | 8 | 20578-818R | 20487-B818R | 20563-S818R | 3/4 | .035 | |
| 18 | 12 | 21510-118R | 21511-B118R | — | 3/4 | .035 | |
| 24 | 4 | 20554-424R | 20490-B424R | 20555-S424R | 3/4 | .035 | |
| 24 | 6 | 20568-624R | 20496-B624R | 20569-S624R | 3/4 | .035 | |
| 24 | 8 | 20579-824R | — | — | 3/4 | .035 | All metals less than 1/8" thick, Tubing, Conduit, Trim |