



SHIELDTEC® STANDARD NON-DETECTABLE TAPE 3” x 1000’

Durable, dependable non-detectable polyethylene warning tape for service and other non-critical metallic installations. Installed at proper shallow depth, ShieldTec is tough, basic protection for any type of buried cable or pipe. Suitable for open trench installation.

INCLUDES:

[\(1\) SHIELDTEC® STANDARD NON-DETECTABLE TAPE \(22-202\)](#)

FEATURES:

- Environmentally safe
- Lead free
- Permanent messaging
- Wear resistant

PRODUCT SPECIFICATIONS:

| Feature | Method | Value (English) | Value (SI) |
|-------------------|---------------|-----------------------------------|------------------------------|
| Overall Thickness | ASTM D-2103 | 4.0 mil (Nominal) | 0.1 mm (Nominal) |
| Weight | ASTM D-2103 | 17.04 lbs / 1,000 ft ² | 8.32 kg / 100 m ² |
| Tensile Strength | ASTM D-882 | Length: 2,565 psi | Length: 17.7 Mpa |
| Elongation | ASTM D-882 | Length: 492% | Length: 492% |
| Printability | ASTM D-2578 | | > 40 dynes |
| Plastic Density | ASTM D-792-08 | | .951 g/cc |



SHIELDTEC® STANDARD NON-DETECTABLE TAPE 3” x 1000’

Durable, dependable non-detectable polyethylene warning tape for service and other non-critical metallic installations. Installed at proper shallow depth, ShieldTec is tough, basic protection for any type of buried cable or pipe. Suitable for open trench installation.

INCLUDES:

[\(1\) SHIELDTEC® STANDARD NON-DETECTABLE TAPE \(22-202\)](#)

FEATURES:

- Environmentally safe
- Lead free
- Permanent messaging
- Wear resistant

PRODUCT SPECIFICATIONS:

| Feature | Method | Value (English) | Value (SI) |
|-------------------|---------------|-----------------------------------|------------------------------|
| Overall Thickness | ASTM D-2103 | 4.0 mil (Nominal) | 0.1 mm (Nominal) |
| Weight | ASTM D-2103 | 17.04 lbs / 1,000 ft ² | 8.32 kg / 100 m ² |
| Tensile Strength | ASTM D-882 | Length: 2,565 psi | Length: 17.7 Mpa |
| Elongation | ASTM D-882 | Length: 492% | Length: 492% |
| Printability | ASTM D-2578 | | > 40 dynes |
| Plastic Density | ASTM D-792-08 | | .951 g/cc |