


Oversize blank box mounted wallplates

Product description


1-Gang, 2-Gang




1-Gang



2-Gang



2-Gang toggle & duplex receptacle



1-Gang with 0.375" hole




GFER



2160



231



153

Blank - box mounted

Description	Material	Color suffix	Catalog no.		
1-Gang	Thermoset	V, W	□ 2729__	•	•
	302/304 Stainless steel	—	□ 93851	•	•
2-Gang	302/304 Stainless steel	—	□ 93852	•	•

Oversize combination wallplates

Product description

2-Gang

Combination 2-gang

Description	Material	Color suffix	Catalog no.		
Toggle & duplex receptacle	Thermoset	B, V, W	□ 2148__	•	•

Oversize telephone & coax wallplates

Product description

2-Gang

Telephone & coax

Description	Material	Color suffix	Catalog no.		
1-Gang with 0.37" (9.5mm) hole	Thermoset	V, W	□ 2728__	•	•
	302/304 Stainless steel	—	□ 93896	•	•

Wallplate accessories

Product description

GFCI extension ring, adapters, wallplate screws & pilot light lamp holder

Wallplate accessories

Description	Material	Color suffix	Catalog no.		
GFCI extension ring for use with GFCIs, 7/8" spacer (cULus)	—	B, BLK, LA, V, W	□ GFER-__**	•	
Adapter - decorator to blank	—	B, LA, V, W	□ 2160__	•	•
Adapter - decorator to toggle	—	V, W	□ 2161__	•	•
Toggle & receptacle wallplate screws #6-32 x 1/2" (12.7mm) for toggle & receptacle wallplates	Baked enamel head/metal	B, LA, V, W	□ 231__	•	
	Nylon	RD, V, W	□ 232__	•	
Toggle & receptacle wallplate screws #6-32 x 5/16" (7.9mm) for toggle & receptacle wallplates	Baked enamel head/metal	LA, V, W	□ 2231__	•	
Recessed pilot light lamp holder with 6 watt clear S-6 bulb (cULus)	—	—	□ 153__**†	•	•

*For use with louver wallplate, ** cULus Listed, † UL Listed, CSA certified

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), BLK (Black), LA (Light Almond), RD (Red), V (Ivory), W (White)



Certification information: 2000, 4000, 5000, ST & PJ series wallplates are cULus Listed; 93000 series wallplates are UL Listed and CSA Certified; 94000 series wallplates are UL Listed and CSA certified. **Specification information:** K-22

Compliances, specifications and availability are subject to change without notice.


Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32


Oversize blank box mounted wallplates

Product description


1-Gang, 2-Gang




1-Gang



2-Gang




2-Gang toggle & duplex receptacle



1-Gang with 0.375" hole




GFER



2160



231



153

Blank - box mounted

Description	Material	Color suffix	Catalog no.		
1-Gang	Thermoset	V, W	□ 2729__	•	•
	302/304 Stainless steel	—	□ 93851	•	•
2-Gang	302/304 Stainless steel	—	□ 93852	•	•

Oversize combination wallplates

Product description

2-Gang

Combination 2-gang

Description	Material	Color suffix	Catalog no.		
Toggle & duplex receptacle	Thermoset	B, V, W	□ 2148__	•	•

Oversize telephone & coax wallplates

Product description

2-Gang

Telephone & coax

Description	Material	Color suffix	Catalog no.		
1-Gang with 0.37" (9.5mm) hole	Thermoset	V, W	□ 2728__	•	•
	302/304 Stainless steel	—	□ 93896	•	•

Wallplate accessories

Product description

GFCI extension ring, adapters, wallplate screws & pilot light lamp holder

Wallplate accessories

Description	Material	Color suffix	Catalog no.		
GFCI extension ring for use with GFCIs, 7/8" spacer (cULus)	—	B, BLK, LA, V, W	□ GFER-__**	•	
Adapter - decorator to blank	—	B, LA, V, W	□ 2160__	•	•
Adapter - decorator to toggle	—	V, W	□ 2161__	•	•
Toggle & receptacle wallplate screws #6-32 x 1/2" (12.7mm) for toggle & receptacle wallplates	Baked enamel head/metal	B, LA, V, W	□ 231__	•	
	Nylon	RD, V, W	□ 232__	•	
Toggle & receptacle wallplate screws #6-32 x 5/16" (7.9mm) for toggle & receptacle wallplates	Baked enamel head/metal	LA, V, W	□ 2231__	•	
Recessed pilot light lamp holder with 6 watt clear S-6 bulb (cULus)	—	—	□ 153__**†	•	•

*For use with louver wallplate, ** cULus Listed, † UL Listed, CSA certified

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), BLK (Black), LA (Light Almond), RD (Red), V (Ivory), W (White)



Certification information: 2000, 4000, 5000, ST & PJ series wallplates are cULus Listed; 93000 series wallplates are UL Listed and CSA Certified; 94000 series wallplates are UL Listed and CSA certified. **Specification information:** K-22

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32