

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Trade Size

234DCI2 1-1/2" Ins Throat Set/Screw Diecast Emt Connector *Bridgeport Fittings*

| Catalog Number | 234DCI2 | | |
|-----------------------------------|---|--|--|
| Manufacturer | Bridgeport Fittings | | |
| Description | Connector, Set Screw, Zinc Die Cast, 105 Degree C Insulated | | |
| | Throat, Size 1-1/2 Inch | | |
| Weight per unit | 38.0 (lbs/each) | | |
| Product Category | Die Cast Insulated Straight Se | | |
| eatures | | | |
| Connector Type | SET SCREW | | |
| insulation | Insulated Throat | | |
| media | Yes | | |
| Material, Color, and Finish | | | |
| Finish | Ball burnish | | |
| imensions and Weight | | | |
| Size | 1 1/2 | | |
| escriptions | | | |
| Description | 1-1/2" INS THROAT SET/SCREW DIECAST EMT CONNECTOR | | |
| extra long description | BPT 234-DCI2 1-1/2 SS CONN. INS. ZI | | |
| Features | Think Orange: Zinc Advantage –Error-free Performance – meets same stringent UL tests as steel. Bridgeport zinc EMT fittings set the standard for EMT. | | |
| Long Description | Connector, Set Screw, Zinc Die Cast, 105 Degree C Insulated Throat, Size 1-1/2 Inch | | |
| Product Type | 1-1/2 SS Conn. Ins. Zinc | | |
| Special Features | Furnished with Tri-Drive Slotted/Phillips/Robertson Screw | | |
| Nanufacturer Information | | | |
| Brand | Bridgeport | | |
| GTIN | 00781747162342 | | |
| Manufacturers Part Number | 234-DCl2 | | |
| UPC | 781747162342 | | |
| axonomies, Classifications, and C | ategories | | |
| | 4.5 | | |
| Category Description | DIECAST EMT FITTINGS | | |
| Category Description Type | DIECAST EMT FITTINGS CONNECTOR | | |

1-1/2



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | Pack | a | gı | n | g |
|-----------|------|---|----|---|---|
|-----------|------|---|----|---|---|

| Carton | 10 | |
|-----------------|-----|--|
| Package | 100 | |
| Weight Per each | 38 | |

Uses, Certifications, and Standards

| cs, oci tilications, and standards | |
|------------------------------------|---|
| Application | Used to secure EMT to box or enclosure. 1/2" thru 1" |
| | concrete-tight, 1-1/4" thru 4" concrete-tight when taped. 2" thru |
| | 4" suitable for use with steel or aluminum EMT. Plastic insulator |
| | rated 105degreeC. |
| standard | UL, CSA |
| standard | rated 105degreeC. |