



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 250A 3P Voltage Protection

*Littelfuse*

Catalog Number	250A
Manufacturer	Littelfuse
Description	The 250A Is A 3-Phase, Auto-Ranging, Dual-Range Voltage Monitor That Protects 190-480VAC, 50*/60HZ Motors Regardless Of Size From Low and High Voltage, Unbalance/Single-Phase, and Reverse-Phase. The Product Provides A User Selectable Nominal Voltage Setpoint and The Voltage Monitor Automatically Selects Between The 200V and 400V Range. The 250A Also Features Adjustable or Manual Restart Delay. This Unique Microcontroller-Based Voltage and Phase-Sensing Device Constantly Monitors The 3-Phase Voltages to Det
Weight per unit	N/A
Product Category	Monitoring Relays & Accy.

### Features

Voltage Rating	190 to 480
----------------	------------

### Descriptions

Description	3P VOLTAGE PROTECTION
extra long description	L-FSE 250A 3-PHASE VOLTAGE MONITOR/
Long Description	The 250A is a 3-phase, auto-ranging, dual-range voltage monitor that protects 190-480VAC, 50*/60Hz motors regardless of size from low and high voltage, unbalance/single-phase, and reverse-phase. The product provides a user selectable nominal voltage setpoint and the voltage monitor automatically selects between the 200V and 400V range. The 250A also features adjustable or manual restart delay. This unique microcontroller-based voltage and phase-sensing device constantly monitors the 3-phase voltages to det
Product Type	3-Phase Voltage Monitor/ 190-4
Special Features	5YR WARR

### Manufacturer Information

Brand	Littelfuse
GTIN	00079458990447
Manufacturers Part Number	250A
sub brand	Symcom
UPC	079458990447

### Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
----------------------	--------------------------



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Weight Per each	0

## Uses, Certifications, and Standards

Operating Temperature	-40 to 158
standard	UL/CSA/CE