

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Trade Size

## **254DCI2 1-1/2" Diecast Emt Insulated Concrete Tight Conn** *Bridgeport Fittings*

Catalog Number	254DCl2
Manufacturer	Bridgeport Fittings
Description	Connector, Compression, Zinc Die Cast, 105 Degree C Insulated Throat, Size 1 1/2 Inch
Weight per unit	0.5400 (lbs/each)
Product Category	Die Cast Insulated Straight CO
eatures	
Connector Type	Compression
insulation	Insulated Throat
Material	Zinc Die Cast
media	Yes
Material, Color, and Finish	
Finish	Ball burnish
imensions and Weight	
Size	1 1/2
	1.17.4
escriptions	1 1/2" DIFCACT FAIT INICH ATED CONCRETE TIGHT CONN.
Description	1-1/2" DIECAST EMT INSULATED CONCRETE TIGHT CONN
extra long description	BPT 254-DCI2 1-1/2" COMP. CONN. INS
Features	Think Orange: Zinc Advantage –Error-free Performance – meets same stringent UL tests as steel. Bridgeport zinc EMT fittings se the standard for EMT.
Long Description	Connector, Compression, Zinc Die Cast, 105 Degree C Insulated
g	Throat, Size 1 1/2 Inch
Product Type	1-1/2" Comp. Conn. Ins. Zinc
Special Features	Concrete-Tight
Manufacturer Information	
Brand	Bridgeport
GTIN	00781747162540
Manufacturers Part Number	254-DCI2
UPC	781747162540
axonomies, Classifications, and (	Categories
Category Description	DIFOACT FAIT FITTINGS
Type	CONNECTOR
rade Size	To Section 2 to Se

1-1/2



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	าดู
-----------	-----

Carton	10	
Package	40	
Weight Per each	0.54	

## **Uses, Certifications, and Standards**

Application	Used to join steel EMT to box or enclosure. Concrete-tight. 1/2" thru 2" suitable for use with Steel or Aluminum EMT. Insulator
	rated 105degree C.
standard	UL, CSA
Temperature Rating	105?°C