



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 257RTI2 3" Raintight Diecast Compression Connector

*Bridgeport Fittings*

|                  |  |
|------------------|--|
| Catalog Number   | 257RTI2                                      |
| Manufacturer     | Bridgeport Fittings                          |
| Description      | 3" Raintight Insulated Connector, NPT Thread |
| Weight per unit  | 1.7 (lbs/each)                               |
| Product Category | Liquid Tight Fittings                        |

### Features

|                |                  |
|----------------|------------------|
| Connector Type | Compression      |
| insulation     | Insulated Throat |
| media          | Yes              |

### Dimensions and Weight

|      |   |
|------|---|
| Size | 3 |
|------|---|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 3" RAINTIGHT DIECAST COMPRESSION CONNECTOR                             |
| extra long description | BPT 257-RTI2 3" RAINTIGHT INS CONNE                                    |
| Features               | Think Orange: Quality In, Water Out. Listed for Damp or Wet Locations. |
| Long Description       | 3" Raintight Insulated Connector, NPT THREAD                           |
| Product Type           | 3" Raintight Ins Connector   |
| Special Features       | The Dual Internal sealing rings create a raintight seal.               |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | Bridgeport     |
| GTIN                      | 00781747192578 |
| Manufacturers Part Number | 257-RTI2       |
| UPC                       | 781747192578   |

### Taxonomies, Classifications, and Categories

|                      |                       |
|----------------------|-----------------------|
| Category Description | METALLIC FITTINGS     |
| Type                 | Raintight Compression |

### Trade Size

|            |   |
|------------|---|
| Trade Size | 3 |
|------------|---|

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 12    |
| Weight Per each | 1.725 |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure. With Bridgeport's newly redesigned Raintight Compression Connectors, 256-RTI2 thru 259-RTI2, contractors can install just one wet location fitting for either thread less Rigid / IMC or EMT. These 3" dual Listed Zinc Alloy fittings come standard with a 105° C temperature rated insulated throat and the words "Rigid / EMT and RAIN TIGHT" clearly cast into the body. Thi

standard

cULus