

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

258DC2 3-1/2" Diecast Emt Concrete Tight Connector *Bridgeport Fittings*

внадерон Fittings	
Catalog Number	258DC2
Manufacturer	Bridgeport Fittings
Description	Connector, Compression, Zinc Die Cast, Size 3 1/2 Inch
Weight per unit	2.5 (lbs/each)
Product Category	Die Cast Uninsulated Straight
Features	
Connector Type	Compression
insulation	None
Material	Zinc Die Cast
media	Yes
Material, Color, and Finish	
Finish	Ball burnish
Dimensions and Weight	
Size	3-1/2
Descriptions	
Description	3-1/2" DIECAST EMT CONCRETE TIGHT CONNECTOR
extra long description	BPT 258-DC2 3 1/2" COMP. CONN.
Features	Think Orange: Zinc Advantage –Error-free Performance – meets same stringent UL tests as steel. Bridgeport zinc EMT fittings set the standard for EMT.
Long Description	Connector, Compression, Zinc Die Cast, Size 3 1/2 Inch
Product Type	3 1/2" Comp. Conn.
Manufacturer Information	
Brand	Bridgeport
GTIN	00781747152589
Manufacturers Part Number	258-DC2
UPC	781747152589
Taxonomies, Classifications, and C	Categories
Category Description	DIECAST EMT FITTINGS
Туре	CONNECTOR
Trade Size	
Trade Size	3-1/2
Packaging	
i askaging	

2.467

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Used to join steel EMT to box or enclosure. Concrete-tight. 2 1/2" thru 4" suitable for use with Steel EMT. 2-1/2" through 4"
	also listed for use with Steel and Aluminum Rigid Conduit.
standard	cULus