

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Catalog Number	27W75
Manufacturer	Pass & Seymour/Legrand
Description	Locking Watertight Connector, 20AMP, 3 250VOLT, Nema Configuration L15-20, Multipoint Sealing System Provides Environmental Protection Of Nema 4, 4X, 6, 6P, and IP67 Rate
Weight per unit	0.8300 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
tures	
amperage rating	20
Cord Type	
Material	Rubber
Number of Wires	4.0
Phase	Three
Poles	3-way
Voltage	250.0 V
Voltage Rating	250
Wire Size	14 - 10 AWG
<b>terial, Color, and Finish</b> Color	Yellow
	Yellow
scriptions	
Description	TURNLOK CONN IP67 20A 3PH 250V L1520R
extra long description	P&S 27W75 TL CONN IP67 20A 3PH 250V
Long Description	Locking Watertight Connector, 20amp, 3 250volt, NEMA Configuration L15-20, multipoint sealing system provides environmental protection of NEMA 4, 4X, 6, 6P, and IP67 rated
Product Type	TL Conn IP67 20A 3PH 250V L1520R
Special Features	Rated watertight for 1,500 psi high-pressure hosedown, P&S
	Turnlok <sup>®</sup> watertight plugs & connectors feature rugged
	construction, multiple seals to ensure protection against the environment and ease of installation.
nufacturer Information	
Brand	LEGRAND-PASS & SEYMOUR
GTIN Manufacture Dart Number	00785007033106
Manufacturers Part Number	27W75
UPC	785007033106
onomies, Classifications, and C	-
Category Description	
	Locking Connector



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Amperage	20.0
Packaging	
Carton	
Package	10
Weight Per each	0.83
Uses, Certifications, and Standards	
Application	High-pressure washdowns. Particle build-up. Condensation. Corrosive substances. Food and beverage processing plants can be harsh, challenging environments. Fortunately, we have a full menu of electrical devices that keep things running smoothly while protecting people and equipment. IEC PIN & SLEEVE DEVICES Watertight Plugs & Connectors ¦ Thermoplastic elastomer body resists water, oils, lubricants and soaps while maintaining NEMA 4, 4X, 6, 6P, and IP65, 66, 67 ratings ¦ Ideal for washdown areas — rated wa
environmental conditions	Moisture Resistance NEMA 4, 4X, 12, 6, 6P/IP65, 66, 67 (Plug & Connector only) Flammability UL94V0 (boxes & wiring device interiors) Operating Temperature -40°C (without impact) to +60°C continuous UV resistance All exposed material s are UV stabilized
nema rating	L15-20R
standard	UL Listed, CSA Listed