



Metalux's GR LED Lensed Troffers offers the ideal balance of LED performance and value. This new series delivers top-tier LED performance, maximizing your energy savings and reducing maintenance cost, while offering the simplicity of our most popular lensed troffer family. With features like spring-loaded hinged door assembly for easy access, GR LED provides the perfect fit for virtually all recessed applications.

Performance

- Available in 2' x 4' (4800, 6400), 2' x 2' (3200, 4300) and 1' x 4' (3200, 4300) sizes
- Two lumen packages per configuration
- Correlated Color Temperatures of 3500K and 4000K
- Class 2, 24V DC constant driver with standard 0-10V dimming
- Typical CRI 85
- Lumen maintenance of L70 at 50,000 hours
- Five-year warranty

Compliances

- LED modules comply with IESNA LM-79 and LM-80 standards
- Listed for IC (Insulated Ceiling)
- cULus listed 1598 for damp locations
- RoHS compliant

Product Controls

GR LED Series is control-friendly, offering compatibility with occupancy and daylight sensors, dimmers and full-scale lighting control systems. Using products from Cooper Controls and others will provide optimal energy savings and extend service life while providing light level flexibility.

- **0-10V Dimmers**

Works with common 0-10V fluorescent wallbox dimmers

- **Lighting Control Panels**

Integrates with lighting control panels' 0-10V (4-wire) modules

- **120/277V Sensors**

Compatible with typical commercial occupancy sensors







Ordering Information

Sample Number: 2GR-LD1-32-A-UNV-L835-CD1-U

Rating	Width	Trim Type	Series	Door Frame	LED Type
[Blank]=Standard ATW-SW4=Chicago Rated	[Blank]=1' Width 2=2' Width	G=Grid/Lay-In (Standard) ¹ G=Concealed T G=Slot Grid	R=General Purpose Troffer	Standard=Flat White Steel Door (Leave Blank) FA=Flat White Extruded Aluminum c/w Spring Latch RA=Regressed White Extruded Aluminum FAN=Flush Natural Anodized Extruded Aluminum RAN=Regressed Natural Anodized Extruded Aluminum FAB=Flush Black Extruded Aluminum RAB=Regressed Black Extruded Aluminum	LD1=LED 1.0
LED Lumens Output ⁶	Shielding	Voltage ²	Options	CCT	Driver Type
32=3200 ⁷ 43=4300 ⁷ 48=4800 ⁸ 64=6400 ⁸	A=A12 .095 A125MIN=A12 .125 MIN A19/156=A19 .156 F=A12 .095 Frost F125=A12 .125 Frost	UNV=Universal Voltage 120-277 ³	GL=Single Element Fuse GM=Double Element Fuse Flex=Flex Installed (Reference Flex Ordering Information) EL=Emergency Installed ^{4,5}	CCT L835=3500K L840=4000K	CD=0-10V Dimming Driver
Number of Drivers	Options	Packaging ⁷	Accessories (Order Separately)		
1=1 Driver	PAF=Painted After Fabrication G1=Gasket, Door Frame and Housing G2=G1 plus Gasket between Lens and Door G3=G1 and G2 plus Gasketing on Mounting Surface of Fixture Trims	PALC=Palletized Fixtures in Carton U=Unit Pack	EQ-CLIP-U=T-BAR Safety Earthquake Clips ¹ DF-22-W=2' x 2' Drywall Frame Kit DF-24-W=2' x 4' Drywall Frame Kit		

NOTES: 1. An EQ Grid Clip is recommended for all 9/16" ceiling systems. 2. Products also available in non-US voltage and frequencies for international markets. 3. Not available when specifying emergencies, voltage must be specific. 4. EL options are non-integral. 5. Call factory. 6. Nominal lumen output. 7. 2' x 2' and 1' x 4' only. 8. 2' x 4' only. Specifications & dimensions subject to change without notice. Consult your Cooper Lighting Representative for availability and ordering information.

Photometrics

2GR-LD1-48-A-UNV-L835-CD1-U	2GR-LD1-64-A-UNV-L835-CD1-U																																																																																																																																																																																																																																																																																																																																						
 <p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance 20%</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <td>70</td><td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> </tr> </thead> <tbody> <tr> <td>RCR</td> <td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td> </tr> <tr> <td>1</td><td>110</td><td>105</td><td>101</td><td>98</td><td>99</td><td>96</td><td>93</td><td>95</td><td>93</td><td>91</td> </tr> <tr> <td>2</td><td>101</td><td>93</td><td>87</td><td>82</td><td>88</td><td>83</td><td>79</td><td>85</td><td>81</td><td>77</td> </tr> <tr> <td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td> </tr> <tr> <td>4</td><td>86</td><td>74</td><td>66</td><td>60</td><td>71</td><td>64</td><td>59</td><td>68</td><td>63</td><td>58</td> </tr> <tr> <td>5</td><td>79</td><td>67</td><td>59</td><td>53</td><td>64</td><td>57</td><td>52</td><td>62</td><td>56</td><td>51</td> </tr> <tr> <td>6</td><td>73</td><td>61</td><td>53</td><td>46</td><td>58</td><td>51</td><td>46</td><td>57</td><td>50</td><td>46</td> </tr> <tr> <td>7</td><td>68</td><td>56</td><td>47</td><td>41</td><td>53</td><td>46</td><td>41</td><td>52</td><td>45</td><td>41</td> </tr> <tr> <td>8</td><td>64</td><td>51</td><td>43</td><td>37</td><td>49</td><td>42</td><td>37</td><td>48</td><td>41</td><td>37</td> </tr> <tr> <td>9</td><td>60</td><td>47</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td><td>44</td><td>38</td><td>33</td> </tr> <tr> <td>10</td><td>56</td><td>43</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td><td>41</td><td>35</td><td>31</td> </tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr> <td>0-30</td> <td>1629</td> <td>33.7</td> </tr> <tr> <td>0-40</td> <td>2607</td> <td>53.9</td> </tr> <tr> <td>0-60</td> <td>4147</td> <td>85.8</td> </tr> <tr> <td>0-90</td> <td>4833</td> <td>100.0</td> </tr> <tr> <td>0-180</td> <td>4833</td> <td>100.0</td> </tr> </tbody> </table> <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 4833 Input Watts = 48.6W Efficacy = 99.4 LPW Test: 2GR-LD1-48-A-UNV-L835-CD1-U.IES</p>	rc	Effective floor cavity reflectance 20%						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	105	101	98	99	96	93	95	93	91	2	101	93	87	82	88	83	79	85	81	77	3	93	83	76	70	79	73	68	76	71	67	4	86	74	66	60	71	64	59	68	63	58	5	79	67	59	53	64	57	52	62	56	51	6	73	61	53	46	58	51	46	57	50	46	7	68	56	47	41	53	46	41	52	45	41	8	64	51	43	37	49	42	37	48	41	37	9	60	47	39	34	45	38	34	44	38	33	10	56	43	36	31	42	35	31	41	35	31	Zone	Lumens	%Fixture	0-30	1629	33.7	0-40	2607	53.9	0-60	4147	85.8	0-90	4833	100.0	0-180	4833	100.0	 <p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance 20%</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <td>70</td><td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> </tr> </thead> <tbody> <tr> <td>RCR</td> <td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td> </tr> <tr> <td>1</td><td>110</td><td>105</td><td>101</td><td>98</td><td>99</td><td>96</td><td>93</td><td>95</td><td>93</td><td>90</td> </tr> <tr> <td>2</td><td>101</td><td>93</td><td>87</td><td>82</td><td>88</td><td>83</td><td>79</td><td>85</td><td>81</td><td>77</td> </tr> <tr> <td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td> </tr> <tr> <td>4</td><td>86</td><td>74</td><td>66</td><td>60</td><td>71</td><td>64</td><td>59</td><td>68</td><td>63</td><td>58</td> </tr> <tr> <td>5</td><td>79</td><td>67</td><td>59</td><td>53</td><td>64</td><td>57</td><td>52</td><td>62</td><td>56</td><td>51</td> </tr> <tr> <td>6</td><td>73</td><td>61</td><td>53</td><td>46</td><td>58</td><td>51</td><td>46</td><td>57</td><td>50</td><td>46</td> </tr> <tr> <td>7</td><td>68</td><td>56</td><td>47</td><td>41</td><td>53</td><td>46</td><td>41</td><td>52</td><td>45</td><td>41</td> </tr> <tr> <td>8</td><td>64</td><td>51</td><td>43</td><td>37</td><td>49</td><td>42</td><td>37</td><td>48</td><td>41</td><td>37</td> </tr> <tr> <td>9</td><td>60</td><td>47</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td><td>44</td><td>38</td><td>33</td> </tr> <tr> <td>10</td><td>56</td><td>43</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td><td>41</td><td>35</td><td>31</td> </tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr> <td>0-30</td> <td>2289</td> <td>33.6</td> </tr> <tr> <td>0-40</td> <td>3666</td> <td>53.8</td> </tr> <tr> <td>0-60</td> <td>5839</td> <td>85.8</td> </tr> <tr> <td>0-90</td> <td>6808</td> <td>100.0</td> </tr> <tr> <td>0-180</td> <td>6808</td> <td>100.0</td> </tr> </tbody> </table> <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 6808 Input Watts = 70.6W Efficacy = 96.4 LPW Test: 2GR-LD1-64-A-UNV-L835-CD1-U.IES</p>	rc	Effective floor cavity reflectance 20%						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	105	101	98	99	96	93	95	93	90	2	101	93	87	82	88	83	79	85	81	77	3	93	83	76	70	79	73	68	76	71	67	4	86	74	66	60	71	64	59	68	63	58	5	79	67	59	53	64	57	52	62	56	51	6	73	61	53	46	58	51	46	57	50	46	7	68	56	47	41	53	46	41	52	45	41	8	64	51	43	37	49	42	37	48	41	37	9	60	47	39	34	45	38	34	44	38	33	10	56	43	36	31	42	35	31	41	35	31	Zone	Lumens	%Fixture	0-30	2289	33.6	0-40	3666	53.8	0-60	5839	85.8	0-90	6808	100.0	0-180	6808	100.0
rc		Effective floor cavity reflectance 20%																																																																																																																																																																																																																																																																																																																																					
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	105	101	98	99	96	93	95	93	91																																																																																																																																																																																																																																																																																																																													
2	101	93	87	82	88	83	79	85	81	77																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	74	66	60	71	64	59	68	63	58																																																																																																																																																																																																																																																																																																																													
5	79	67	59	53	64	57	52	62	56	51																																																																																																																																																																																																																																																																																																																													
6	73	61	53	46	58	51	46	57	50	46																																																																																																																																																																																																																																																																																																																													
7	68	56	47	41	53	46	41	52	45	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	37	49	42	37	48	41	37																																																																																																																																																																																																																																																																																																																													
9	60	47	39	34	45	38	34	44	38	33																																																																																																																																																																																																																																																																																																																													
10	56	43	36	31	42	35	31	41	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	1629	33.7																																																																																																																																																																																																																																																																																																																																					
0-40	2607	53.9																																																																																																																																																																																																																																																																																																																																					
0-60	4147	85.8																																																																																																																																																																																																																																																																																																																																					
0-90	4833	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	4833	100.0																																																																																																																																																																																																																																																																																																																																					
rc	Effective floor cavity reflectance 20%																																																																																																																																																																																																																																																																																																																																						
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	105	101	98	99	96	93	95	93	90																																																																																																																																																																																																																																																																																																																													
2	101	93	87	82	88	83	79	85	81	77																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	74	66	60	71	64	59	68	63	58																																																																																																																																																																																																																																																																																																																													
5	79	67	59	53	64	57	52	62	56	51																																																																																																																																																																																																																																																																																																																													
6	73	61	53	46	58	51	46	57	50	46																																																																																																																																																																																																																																																																																																																													
7	68	56	47	41	53	46	41	52	45	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	37	49	42	37	48	41	37																																																																																																																																																																																																																																																																																																																													
9	60	47	39	34	45	38	34	44	38	33																																																																																																																																																																																																																																																																																																																													
10	56	43	36	31	42	35	31	41	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	2289	33.6																																																																																																																																																																																																																																																																																																																																					
0-40	3666	53.8																																																																																																																																																																																																																																																																																																																																					
0-60	5839	85.8																																																																																																																																																																																																																																																																																																																																					
0-90	6808	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	6808	100.0																																																																																																																																																																																																																																																																																																																																					
 <p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance 20%</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <td>70</td><td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> </tr> </thead> <tbody> <tr> <td>RCR</td> <td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td> </tr> <tr> <td>1</td><td>110</td><td>106</td><td>102</td><td>98</td><td>99</td><td>96</td><td>94</td><td>95</td><td>93</td><td>91</td> </tr> <tr> <td>2</td><td>101</td><td>94</td><td>87</td><td>82</td><td>88</td><td>84</td><td>79</td><td>85</td><td>81</td><td>78</td> </tr> <tr> <td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td> </tr> <tr> <td>4</td><td>86</td><td>75</td><td>67</td><td>61</td><td>71</td><td>65</td><td>59</td><td>69</td><td>63</td><td>59</td> </tr> <tr> <td>5</td><td>79</td><td>68</td><td>59</td><td>53</td><td>64</td><td>58</td><td>52</td><td>63</td><td>56</td><td>52</td> </tr> <tr> <td>6</td><td>74</td><td>61</td><td>53</td><td>47</td><td>59</td><td>52</td><td>46</td><td>57</td><td>51</td><td>46</td> </tr> <tr> <td>7</td><td>69</td><td>56</td><td>48</td><td>42</td><td>54</td><td>47</td><td>42</td><td>52</td><td>46</td><td>41</td> </tr> <tr> <td>8</td><td>64</td><td>51</td><td>43</td><td>38</td><td>49</td><td>43</td><td>38</td><td>48</td><td>42</td><td>37</td> </tr> <tr> <td>9</td><td>60</td><td>47</td><td>40</td><td>34</td><td>46</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td> </tr> <tr> <td>10</td><td>57</td><td>44</td><td>36</td><td>31</td><td>42</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td> </tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr> <td>0-30</td> <td>1115</td> <td>34.6</td> </tr> <tr> <td>0-40</td> <td>1170</td> <td>55.0</td> </tr> <tr> <td>0-60</td> <td>2772</td> <td>86.1</td> </tr> <tr> <td>0-90</td> <td>3221</td> <td>100.0</td> </tr> <tr> <td>0-180</td> <td>3221</td> <td>100.0</td> </tr> </tbody> </table> <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 3221 Input Watts = 36.2W Efficacy = 89 LPW Test: 2GR-LD1-32-A-UNV-L835-CD1-U.IES</p>	rc	Effective floor cavity reflectance 20%						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	106	102	98	99	96	94	95	93	91	2	101	94	87	82	88	84	79	85	81	78	3	93	83	76	70	79	73	68	76	71	67	4	86	75	67	61	71	65	59	69	63	59	5	79	68	59	53	64	58	52	63	56	52	6	74	61	53	47	59	52	46	57	51	46	7	69	56	48	42	54	47	42	52	46	41	8	64	51	43	38	49	43	38	48	42	37	9	60	47	40	34	46	39	34	45	38	34	10	57	44	36	31	42	36	31	42	35	31	Zone	Lumens	%Fixture	0-30	1115	34.6	0-40	1170	55.0	0-60	2772	86.1	0-90	3221	100.0	0-180	3221	100.0	 <p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance 20%</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <td>70</td><td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> <td>50</td><td>30</td><td>10</td> </tr> </thead> <tbody> <tr> <td>RCR</td> <td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td> </tr> <tr> <td>1</td><td>110</td><td>106</td><td>102</td><td>98</td><td>99</td><td>96</td><td>94</td><td>95</td><td>93</td><td>91</td> </tr> <tr> <td>2</td><td>101</td><td>94</td><td>87</td><td>82</td><td>88</td><td>83</td><td>79</td><td>85</td><td>81</td><td>78</td> </tr> <tr> <td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td> </tr> <tr> <td>4</td><td>86</td><td>75</td><td>67</td><td>61</td><td>71</td><td>65</td><td>59</td><td>69</td><td>63</td><td>59</td> </tr> <tr> <td>5</td><td>79</td><td>68</td><td>59</td><td>53</td><td>64</td><td>58</td><td>52</td><td>63</td><td>56</td><td>52</td> </tr> <tr> <td>6</td><td>74</td><td>61</td><td>53</td><td>47</td><td>59</td><td>52</td><td>46</td><td>57</td><td>51</td><td>46</td> </tr> <tr> <td>7</td><td>69</td><td>56</td><td>48</td><td>42</td><td>54</td><td>47</td><td>42</td><td>52</td><td>46</td><td>41</td> </tr> <tr> <td>8</td><td>64</td><td>51</td><td>43</td><td>38</td><td>49</td><td>43</td><td>38</td><td>48</td><td>42</td><td>37</td> </tr> <tr> <td>9</td><td>60</td><td>47</td><td>40</td><td>34</td><td>46</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td> </tr> <tr> <td>10</td><td>57</td><td>44</td><td>36</td><td>31</td><td>42</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td> </tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr> <td>0-30</td> <td>1505</td> <td>34.6</td> </tr> <tr> <td>0-40</td> <td>2389</td> <td>54.9</td> </tr> <tr> <td>0-60</td> <td>3744</td> <td>86.1</td> </tr> <tr> <td>0-90</td> <td>4351</td> <td>100.0</td> </tr> <tr> <td>0-180</td> <td>4351</td> <td>100.0</td> </tr> </tbody> </table> <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 4351 Input Watts = 48.9W Efficacy = 89 LPW Test: 2GR-LD1-43-A-UNV-L835-CD1-U.IES</p>	rc	Effective floor cavity reflectance 20%						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	106	102	98	99	96	94	95	93	91	2	101	94	87	82	88	83	79	85	81	78	3	93	83	76	70	79	73	68	76	71	67	4	86	75	67	61	71	65	59	69	63	59	5	79	68	59	53	64	58	52	63	56	52	6	74	61	53	47	59	52	46	57	51	46	7	69	56	48	42	54	47	42	52	46	41	8	64	51	43	38	49	43	38	48	42	37	9	60	47	40	34	46	39	34	45	38	34	10	57	44	36	31	42	36	31	42	35	31	Zone	Lumens	%Fixture	0-30	1505	34.6	0-40	2389	54.9	0-60	3744	86.1	0-90	4351	100.0	0-180	4351	100.0
rc		Effective floor cavity reflectance 20%																																																																																																																																																																																																																																																																																																																																					
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	106	102	98	99	96	94	95	93	91																																																																																																																																																																																																																																																																																																																													
2	101	94	87	82	88	84	79	85	81	78																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	75	67	61	71	65	59	69	63	59																																																																																																																																																																																																																																																																																																																													
5	79	68	59	53	64	58	52	63	56	52																																																																																																																																																																																																																																																																																																																													
6	74	61	53	47	59	52	46	57	51	46																																																																																																																																																																																																																																																																																																																													
7	69	56	48	42	54	47	42	52	46	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	38	49	43	38	48	42	37																																																																																																																																																																																																																																																																																																																													
9	60	47	40	34	46	39	34	45	38	34																																																																																																																																																																																																																																																																																																																													
10	57	44	36	31	42	36	31	42	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	1115	34.6																																																																																																																																																																																																																																																																																																																																					
0-40	1170	55.0																																																																																																																																																																																																																																																																																																																																					
0-60	2772	86.1																																																																																																																																																																																																																																																																																																																																					
0-90	3221	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	3221	100.0																																																																																																																																																																																																																																																																																																																																					
rc	Effective floor cavity reflectance 20%																																																																																																																																																																																																																																																																																																																																						
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	106	102	98	99	96	94	95	93	91																																																																																																																																																																																																																																																																																																																													
2	101	94	87	82	88	83	79	85	81	78																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	75	67	61	71	65	59	69	63	59																																																																																																																																																																																																																																																																																																																													
5	79	68	59	53	64	58	52	63	56	52																																																																																																																																																																																																																																																																																																																													
6	74	61	53	47	59	52	46	57	51	46																																																																																																																																																																																																																																																																																																																													
7	69	56	48	42	54	47	42	52	46	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	38	49	43	38	48	42	37																																																																																																																																																																																																																																																																																																																													
9	60	47	40	34	46	39	34	45	38	34																																																																																																																																																																																																																																																																																																																													
10	57	44	36	31	42	36	31	42	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	1505	34.6																																																																																																																																																																																																																																																																																																																																					
0-40	2389	54.9																																																																																																																																																																																																																																																																																																																																					
0-60	3744	86.1																																																																																																																																																																																																																																																																																																																																					
0-90	4351	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	4351	100.0																																																																																																																																																																																																																																																																																																																																					



Metalux's GR LED Lensed Troffers offers the ideal balance of LED performance and value. This new series delivers top-tier LED performance, maximizing your energy savings and reducing maintenance cost, while offering the simplicity of our most popular lensed troffer family. With features like spring-loaded hinged door assembly for easy access, GR LED provides the perfect fit for virtually all recessed applications.

Performance

- Available in 2' x 4' (4800, 6400), 2' x 2' (3200, 4300) and 1' x 4' (3200, 4300) sizes
- Two lumen packages per configuration
- Correlated Color Temperatures of 3500K and 4000K
- Class 2, 24V DC constant driver with standard 0-10V dimming
- Typical CRI 85
- Lumen maintenance of L70 at 50,000 hours
- Five-year warranty

Compliances

- LED modules comply with IESNA LM-79 and LM-80 standards
- Listed for IC (Insulated Ceiling)
- cULus listed 1598 for damp locations
- RoHS compliant

Product Controls

GR LED Series is control-friendly, offering compatibility with occupancy and daylight sensors, dimmers and full-scale lighting control systems. Using products from Cooper Controls and others will provide optimal energy savings and extend service life while providing light level flexibility.

- **0-10V Dimmers**

Works with common 0-10V fluorescent wallbox dimmers

- **Lighting Control Panels**

Integrates with lighting control panels' 0-10V (4-wire) modules

- **120/277V Sensors**

Compatible with typical commercial occupancy sensors







Ordering Information

Sample Number: 2GR-LD1-32-A-UNV-L835-CD1-U

Rating	Width	Trim Type	Series	Door Frame	LED Type
[Blank]=Standard ATW-SW4=Chicago Rated	[Blank]=1' Width 2=2' Width	G=Grid/Lay-In (Standard) ¹ G=Concealed T G=Slot Grid	R=General Purpose Troffer	Standard=Flat White Steel Door (Leave Blank) FA=Flat White Extruded Aluminum c/w Spring Latch RA=Regressed White Extruded Aluminum FAN=Flush Natural Anodized Extruded Aluminum RAN=Regressed Natural Anodized Extruded Aluminum FAB=Flush Black Extruded Aluminum RAB=Regressed Black Extruded Aluminum	LD1=LED 1.0
LED Lumens Output ⁶	Shielding	Voltage ²	Options		Driver Type
32=3200 ⁷ 43=4300 ⁷ 48=4800 ⁸ 64=6400 ⁸	A=A12 .095 A125MIN=A12 .125 MIN A19/156=A19 .156 F=A12 .095 Frost F125=A12 .125 Frost	UNV=Universal Voltage 120-277 ³	GL=Single Element Fuse GM=Double Element Fuse Flex=Flex Installed (Reference Flex Ordering Information) EL=Emergency Installed ^{4,5}		CCT L835=3500K L840=4000K CD=0-10V Dimming Driver
Number of Drivers	Options	Packaging ⁷		Accessories (Order Separately)	
1=1 Driver	PAF=Painted After Fabrication G1=Gasket, Door Frame and Housing G2=G1 plus Gasket between Lens and Door G3=G1 and G2 plus Gasketing on Mounting Surface of Fixture Trims	PALC=Palletized Fixtures in Carton U=Unit Pack		EQ-CLIP-U=T-BAR Safety Earthquake Clips ¹ DF-22-W=2' x 2' Drywall Frame Kit DF-24-W=2' x 4' Drywall Frame Kit	

NOTES: 1. An EQ Grid Clip is recommended for all 9/16" ceiling systems. 2. Products also available in non-US voltage and frequencies for international markets. 3. Not available when specifying emergencies, voltage must be specific. 4. EL options are non-integral. 5. Call factory. 6. Nominal lumen output. 7. 2' x 2' and 1' x 4' only. 8. 2' x 4' only. Specifications & dimensions subject to change without notice. Consult your Cooper Lighting Representative for availability and ordering information.

Photometrics

2GR-LD1-48-A-UNV-L835-CD1-U	2GR-LD1-64-A-UNV-L835-CD1-U																																																																																																																																																																																																																																																																																																																																						
 <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 4833 Input Watts = 48.6W Efficacy = 99.4 LPW Test: 2GR-LD1-48-A-UNV-L835-CD1-U.IES</p>	 <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 6808 Input Watts = 70.6W Efficacy = 96.4 LPW Test: 2GR-LD1-64-A-UNV-L835-CD1-U.IES</p>																																																																																																																																																																																																																																																																																																																																						
<p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <th>70</th><th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> </tr> </thead> <tbody> <tr><td>RCR</td><td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td></tr> <tr><td>1</td><td>110</td><td>105</td><td>101</td><td>98</td><td>99</td><td>96</td><td>93</td><td>95</td><td>93</td><td>91</td></tr> <tr><td>2</td><td>101</td><td>93</td><td>87</td><td>82</td><td>88</td><td>83</td><td>79</td><td>85</td><td>81</td><td>77</td></tr> <tr><td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td></tr> <tr><td>4</td><td>86</td><td>74</td><td>66</td><td>60</td><td>71</td><td>64</td><td>59</td><td>68</td><td>63</td><td>58</td></tr> <tr><td>5</td><td>79</td><td>67</td><td>59</td><td>53</td><td>64</td><td>57</td><td>52</td><td>62</td><td>56</td><td>51</td></tr> <tr><td>6</td><td>73</td><td>61</td><td>53</td><td>46</td><td>58</td><td>51</td><td>46</td><td>57</td><td>50</td><td>46</td></tr> <tr><td>7</td><td>68</td><td>56</td><td>47</td><td>41</td><td>53</td><td>46</td><td>41</td><td>52</td><td>45</td><td>41</td></tr> <tr><td>8</td><td>64</td><td>51</td><td>43</td><td>37</td><td>49</td><td>42</td><td>37</td><td>48</td><td>41</td><td>37</td></tr> <tr><td>9</td><td>60</td><td>47</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td><td>44</td><td>38</td><td>33</td></tr> <tr><td>10</td><td>56</td><td>43</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td><td>41</td><td>35</td><td>31</td></tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr><td>0-30</td><td>1629</td><td>33.7</td></tr> <tr><td>0-40</td><td>2607</td><td>53.9</td></tr> <tr><td>0-60</td><td>4147</td><td>85.8</td></tr> <tr><td>0-90</td><td>4833</td><td>100.0</td></tr> <tr><td>0-180</td><td>4833</td><td>100.0</td></tr> </tbody> </table>	rc	Effective floor cavity reflectance						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	105	101	98	99	96	93	95	93	91	2	101	93	87	82	88	83	79	85	81	77	3	93	83	76	70	79	73	68	76	71	67	4	86	74	66	60	71	64	59	68	63	58	5	79	67	59	53	64	57	52	62	56	51	6	73	61	53	46	58	51	46	57	50	46	7	68	56	47	41	53	46	41	52	45	41	8	64	51	43	37	49	42	37	48	41	37	9	60	47	39	34	45	38	34	44	38	33	10	56	43	36	31	42	35	31	41	35	31	Zone	Lumens	%Fixture	0-30	1629	33.7	0-40	2607	53.9	0-60	4147	85.8	0-90	4833	100.0	0-180	4833	100.0	<p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <th>70</th><th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> </tr> </thead> <tbody> <tr><td>RCR</td><td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td></tr> <tr><td>1</td><td>110</td><td>105</td><td>101</td><td>98</td><td>99</td><td>96</td><td>93</td><td>95</td><td>93</td><td>90</td></tr> <tr><td>2</td><td>101</td><td>93</td><td>87</td><td>82</td><td>88</td><td>83</td><td>79</td><td>85</td><td>81</td><td>77</td></tr> <tr><td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td></tr> <tr><td>4</td><td>86</td><td>74</td><td>66</td><td>60</td><td>71</td><td>64</td><td>59</td><td>68</td><td>63</td><td>58</td></tr> <tr><td>5</td><td>79</td><td>67</td><td>59</td><td>53</td><td>64</td><td>57</td><td>52</td><td>62</td><td>56</td><td>51</td></tr> <tr><td>6</td><td>73</td><td>61</td><td>52</td><td>46</td><td>58</td><td>51</td><td>46</td><td>57</td><td>50</td><td>45</td></tr> <tr><td>7</td><td>68</td><td>56</td><td>47</td><td>41</td><td>53</td><td>46</td><td>41</td><td>52</td><td>45</td><td>41</td></tr> <tr><td>8</td><td>64</td><td>51</td><td>43</td><td>37</td><td>49</td><td>42</td><td>37</td><td>48</td><td>41</td><td>37</td></tr> <tr><td>9</td><td>60</td><td>47</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td><td>44</td><td>38</td><td>33</td></tr> <tr><td>10</td><td>56</td><td>43</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td><td>41</td><td>35</td><td>30</td></tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr><td>0-30</td><td>2289</td><td>33.6</td></tr> <tr><td>0-40</td><td>3666</td><td>53.8</td></tr> <tr><td>0-60</td><td>5839</td><td>85.8</td></tr> <tr><td>0-90</td><td>6808</td><td>100.0</td></tr> <tr><td>0-180</td><td>6808</td><td>100.0</td></tr> </tbody> </table>	rc	Effective floor cavity reflectance						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	105	101	98	99	96	93	95	93	90	2	101	93	87	82	88	83	79	85	81	77	3	93	83	76	70	79	73	68	76	71	67	4	86	74	66	60	71	64	59	68	63	58	5	79	67	59	53	64	57	52	62	56	51	6	73	61	52	46	58	51	46	57	50	45	7	68	56	47	41	53	46	41	52	45	41	8	64	51	43	37	49	42	37	48	41	37	9	60	47	39	34	45	38	34	44	38	33	10	56	43	36	31	42	35	31	41	35	30	Zone	Lumens	%Fixture	0-30	2289	33.6	0-40	3666	53.8	0-60	5839	85.8	0-90	6808	100.0	0-180	6808	100.0
rc		Effective floor cavity reflectance																																																																																																																																																																																																																																																																																																																																					
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	105	101	98	99	96	93	95	93	91																																																																																																																																																																																																																																																																																																																													
2	101	93	87	82	88	83	79	85	81	77																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	74	66	60	71	64	59	68	63	58																																																																																																																																																																																																																																																																																																																													
5	79	67	59	53	64	57	52	62	56	51																																																																																																																																																																																																																																																																																																																													
6	73	61	53	46	58	51	46	57	50	46																																																																																																																																																																																																																																																																																																																													
7	68	56	47	41	53	46	41	52	45	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	37	49	42	37	48	41	37																																																																																																																																																																																																																																																																																																																													
9	60	47	39	34	45	38	34	44	38	33																																																																																																																																																																																																																																																																																																																													
10	56	43	36	31	42	35	31	41	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	1629	33.7																																																																																																																																																																																																																																																																																																																																					
0-40	2607	53.9																																																																																																																																																																																																																																																																																																																																					
0-60	4147	85.8																																																																																																																																																																																																																																																																																																																																					
0-90	4833	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	4833	100.0																																																																																																																																																																																																																																																																																																																																					
rc	Effective floor cavity reflectance																																																																																																																																																																																																																																																																																																																																						
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	105	101	98	99	96	93	95	93	90																																																																																																																																																																																																																																																																																																																													
2	101	93	87	82	88	83	79	85	81	77																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	74	66	60	71	64	59	68	63	58																																																																																																																																																																																																																																																																																																																													
5	79	67	59	53	64	57	52	62	56	51																																																																																																																																																																																																																																																																																																																													
6	73	61	52	46	58	51	46	57	50	45																																																																																																																																																																																																																																																																																																																													
7	68	56	47	41	53	46	41	52	45	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	37	49	42	37	48	41	37																																																																																																																																																																																																																																																																																																																													
9	60	47	39	34	45	38	34	44	38	33																																																																																																																																																																																																																																																																																																																													
10	56	43	36	31	42	35	31	41	35	30																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	2289	33.6																																																																																																																																																																																																																																																																																																																																					
0-40	3666	53.8																																																																																																																																																																																																																																																																																																																																					
0-60	5839	85.8																																																																																																																																																																																																																																																																																																																																					
0-90	6808	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	6808	100.0																																																																																																																																																																																																																																																																																																																																					
<p>2GR-LD1-32-A-UNV-L835-CD1-U</p>  <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 3221 Input Watts = 36.2W Efficacy = 89 LPW Test: 2GR-LD1-32-A-UNV-L835-CD1-U.IES</p>	<p>2GR-LD1-43-A-UNV-L835-CD1-U</p>  <p>Dimming Driver Linear LED 3500K Spacing criterion: (H) 1.2 x mounting height, (L) 1.2 x mounting height Efficiency = 100% Lumens = 4351 Input Watts = 48.9W Efficacy = 89 LPW Test: 2GR-LD1-43-A-UNV-L835-CD1-U.IES</p>																																																																																																																																																																																																																																																																																																																																						
<p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <th>70</th><th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> </tr> </thead> <tbody> <tr><td>RCR</td><td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td></tr> <tr><td>1</td><td>110</td><td>106</td><td>102</td><td>98</td><td>99</td><td>96</td><td>94</td><td>95</td><td>93</td><td>91</td></tr> <tr><td>2</td><td>101</td><td>94</td><td>87</td><td>82</td><td>88</td><td>84</td><td>79</td><td>85</td><td>81</td><td>78</td></tr> <tr><td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td></tr> <tr><td>4</td><td>86</td><td>75</td><td>67</td><td>61</td><td>71</td><td>65</td><td>59</td><td>69</td><td>63</td><td>59</td></tr> <tr><td>5</td><td>79</td><td>68</td><td>59</td><td>53</td><td>64</td><td>58</td><td>52</td><td>63</td><td>56</td><td>52</td></tr> <tr><td>6</td><td>74</td><td>61</td><td>53</td><td>47</td><td>59</td><td>52</td><td>46</td><td>57</td><td>51</td><td>46</td></tr> <tr><td>7</td><td>69</td><td>56</td><td>48</td><td>42</td><td>54</td><td>47</td><td>42</td><td>52</td><td>46</td><td>41</td></tr> <tr><td>8</td><td>64</td><td>51</td><td>43</td><td>38</td><td>49</td><td>43</td><td>38</td><td>48</td><td>42</td><td>37</td></tr> <tr><td>9</td><td>60</td><td>47</td><td>40</td><td>34</td><td>46</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td></tr> <tr><td>10</td><td>57</td><td>44</td><td>36</td><td>31</td><td>42</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td></tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr><td>0-30</td><td>1115</td><td>34.6</td></tr> <tr><td>0-40</td><td>1170</td><td>55.0</td></tr> <tr><td>0-60</td><td>2772</td><td>86.1</td></tr> <tr><td>0-90</td><td>3221</td><td>100.0</td></tr> <tr><td>0-180</td><td>3221</td><td>100.0</td></tr> </tbody> </table>	rc	Effective floor cavity reflectance						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	106	102	98	99	96	94	95	93	91	2	101	94	87	82	88	84	79	85	81	78	3	93	83	76	70	79	73	68	76	71	67	4	86	75	67	61	71	65	59	69	63	59	5	79	68	59	53	64	58	52	63	56	52	6	74	61	53	47	59	52	46	57	51	46	7	69	56	48	42	54	47	42	52	46	41	8	64	51	43	38	49	43	38	48	42	37	9	60	47	40	34	46	39	34	45	38	34	10	57	44	36	31	42	36	31	42	35	31	Zone	Lumens	%Fixture	0-30	1115	34.6	0-40	1170	55.0	0-60	2772	86.1	0-90	3221	100.0	0-180	3221	100.0	<p>Coefficients of Utilization</p> <table border="1"> <thead> <tr> <th rowspan="2">rc</th> <th colspan="6">Effective floor cavity reflectance</th> </tr> <tr> <th colspan="2">80%</th> <th colspan="2">50%</th> <th colspan="2">30%</th> </tr> <tr> <th>rw</th> <th>70</th><th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> <th>50</th><th>30</th><th>10</th> </tr> </thead> <tbody> <tr><td>RCR</td><td>0</td><td>119</td><td>119</td><td>119</td><td>111</td><td>111</td><td>111</td><td>106</td><td>106</td><td>106</td></tr> <tr><td>1</td><td>110</td><td>106</td><td>102</td><td>98</td><td>99</td><td>96</td><td>94</td><td>95</td><td>93</td><td>91</td></tr> <tr><td>2</td><td>101</td><td>94</td><td>87</td><td>82</td><td>88</td><td>83</td><td>79</td><td>85</td><td>81</td><td>78</td></tr> <tr><td>3</td><td>93</td><td>83</td><td>76</td><td>70</td><td>79</td><td>73</td><td>68</td><td>76</td><td>71</td><td>67</td></tr> <tr><td>4</td><td>86</td><td>75</td><td>67</td><td>61</td><td>71</td><td>65</td><td>59</td><td>69</td><td>63</td><td>59</td></tr> <tr><td>5</td><td>79</td><td>68</td><td>59</td><td>53</td><td>64</td><td>58</td><td>52</td><td>63</td><td>56</td><td>52</td></tr> <tr><td>6</td><td>74</td><td>61</td><td>53</td><td>47</td><td>59</td><td>52</td><td>46</td><td>57</td><td>51</td><td>46</td></tr> <tr><td>7</td><td>69</td><td>56</td><td>48</td><td>42</td><td>54</td><td>47</td><td>42</td><td>52</td><td>46</td><td>41</td></tr> <tr><td>8</td><td>64</td><td>51</td><td>43</td><td>38</td><td>49</td><td>43</td><td>38</td><td>48</td><td>42</td><td>37</td></tr> <tr><td>9</td><td>60</td><td>47</td><td>40</td><td>34</td><td>46</td><td>39</td><td>34</td><td>45</td><td>38</td><td>34</td></tr> <tr><td>10</td><td>57</td><td>44</td><td>36</td><td>31</td><td>42</td><td>36</td><td>31</td><td>42</td><td>35</td><td>31</td></tr> </tbody> </table> <p>Zonal Lumen Summary</p> <table border="1"> <thead> <tr> <th>Zone</th> <th>Lumens</th> <th>%Fixture</th> </tr> </thead> <tbody> <tr><td>0-30</td><td>1505</td><td>34.6</td></tr> <tr><td>0-40</td><td>2389</td><td>54.9</td></tr> <tr><td>0-60</td><td>3744</td><td>86.1</td></tr> <tr><td>0-90</td><td>4351</td><td>100.0</td></tr> <tr><td>0-180</td><td>4351</td><td>100.0</td></tr> </tbody> </table>	rc	Effective floor cavity reflectance						80%		50%		30%		rw	70	50	30	10	50	30	10	50	30	10	RCR	0	119	119	119	111	111	111	106	106	106	1	110	106	102	98	99	96	94	95	93	91	2	101	94	87	82	88	83	79	85	81	78	3	93	83	76	70	79	73	68	76	71	67	4	86	75	67	61	71	65	59	69	63	59	5	79	68	59	53	64	58	52	63	56	52	6	74	61	53	47	59	52	46	57	51	46	7	69	56	48	42	54	47	42	52	46	41	8	64	51	43	38	49	43	38	48	42	37	9	60	47	40	34	46	39	34	45	38	34	10	57	44	36	31	42	36	31	42	35	31	Zone	Lumens	%Fixture	0-30	1505	34.6	0-40	2389	54.9	0-60	3744	86.1	0-90	4351	100.0	0-180	4351	100.0
rc		Effective floor cavity reflectance																																																																																																																																																																																																																																																																																																																																					
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	106	102	98	99	96	94	95	93	91																																																																																																																																																																																																																																																																																																																													
2	101	94	87	82	88	84	79	85	81	78																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	75	67	61	71	65	59	69	63	59																																																																																																																																																																																																																																																																																																																													
5	79	68	59	53	64	58	52	63	56	52																																																																																																																																																																																																																																																																																																																													
6	74	61	53	47	59	52	46	57	51	46																																																																																																																																																																																																																																																																																																																													
7	69	56	48	42	54	47	42	52	46	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	38	49	43	38	48	42	37																																																																																																																																																																																																																																																																																																																													
9	60	47	40	34	46	39	34	45	38	34																																																																																																																																																																																																																																																																																																																													
10	57	44	36	31	42	36	31	42	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	1115	34.6																																																																																																																																																																																																																																																																																																																																					
0-40	1170	55.0																																																																																																																																																																																																																																																																																																																																					
0-60	2772	86.1																																																																																																																																																																																																																																																																																																																																					
0-90	3221	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	3221	100.0																																																																																																																																																																																																																																																																																																																																					
rc	Effective floor cavity reflectance																																																																																																																																																																																																																																																																																																																																						
	80%		50%		30%																																																																																																																																																																																																																																																																																																																																		
rw	70	50	30	10	50	30	10	50	30	10																																																																																																																																																																																																																																																																																																																													
RCR	0	119	119	119	111	111	111	106	106	106																																																																																																																																																																																																																																																																																																																													
1	110	106	102	98	99	96	94	95	93	91																																																																																																																																																																																																																																																																																																																													
2	101	94	87	82	88	83	79	85	81	78																																																																																																																																																																																																																																																																																																																													
3	93	83	76	70	79	73	68	76	71	67																																																																																																																																																																																																																																																																																																																													
4	86	75	67	61	71	65	59	69	63	59																																																																																																																																																																																																																																																																																																																													
5	79	68	59	53	64	58	52	63	56	52																																																																																																																																																																																																																																																																																																																													
6	74	61	53	47	59	52	46	57	51	46																																																																																																																																																																																																																																																																																																																													
7	69	56	48	42	54	47	42	52	46	41																																																																																																																																																																																																																																																																																																																													
8	64	51	43	38	49	43	38	48	42	37																																																																																																																																																																																																																																																																																																																													
9	60	47	40	34	46	39	34	45	38	34																																																																																																																																																																																																																																																																																																																													
10	57	44	36	31	42	36	31	42	35	31																																																																																																																																																																																																																																																																																																																													
Zone	Lumens	%Fixture																																																																																																																																																																																																																																																																																																																																					
0-30	1505	34.6																																																																																																																																																																																																																																																																																																																																					
0-40	2389	54.9																																																																																																																																																																																																																																																																																																																																					
0-60	3744	86.1																																																																																																																																																																																																																																																																																																																																					
0-90	4351	100.0																																																																																																																																																																																																																																																																																																																																					
0-180	4351	100.0																																																																																																																																																																																																																																																																																																																																					