

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



30030 Noalox (8 Oz. Bottle) *Ideal*

Catalog Number	30030
Manufacturer	Ideal
Description	Anti-Oxidant Compound, 8 Oz Squeeze Bottle, Petroleum Base, 1.04 Specific Gravity, 310 °F Flash Point, 0.6 LB
Weight per unit	0.6000 (lbs/each)
Product Category	Paint, Chemicals, Etc.
Features	
specific gravity	1,04
Dimensions and Weight	
Size	8 OZ Squeeze Bottle
Descriptions	·
Description	NOALOX (8 OZ. BOTTLE)
extra long description	IDEAL 30-030 NOALOX ANTI-OXIDANT 80
Features	IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-type wire connectors.
Special Features	Anti-oxidant and anti-seizing compound improves efficiency and service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service life of aluminum ele



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer I	Information
----------------	-------------

Brand	Ideal	
GTIN	00783250300303	
sub brand	Noalox	
UPC	783250300303	

Taxonomies, Classifications, and Categories

Category Description	WIRE LUBE, MARKERS, & TIES
Туре	Anti-Oxidant Compound

Packaging

S. Cag. 1.9	
Carton 1	
Package 10	
Weight Per each 0.6	

Uses, Certifications, and Standards

standard	UL LIST	sted	