

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

Fax: 936-560-4685



30031 Noalox (8 Oz. Brush-Cap Bottle)

Catalog Number	30031	
Manufacturer	ldeal	
Description	Anti-Oxidant Compound, 8 Oz Bottle, Petroleum Base, 1.04 Specific Gravity, 310 °F Flash Point, 0.63 LB	
Weight per unit	0 (222 (lbs/sask)	
Product Category	Paint, Chemicals, Etc.	

Features

specific gravity 1.04

Dimensions and Weight

Size 8 OZ Bottle With Brush In Cap

Descriptions

Description	NOALOX (8 OZ. BRUSH-CAP BOTTLE)
extra long description	IDEAL 30-031 NOALOX-8 OZ BRUSH CAP
Features	IDEAL Noalox Anti-Oxidant compound improves efficiency and

IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-type

wire connectors.

Special Features Anti-oxidant and anti-seizing compound improves efficiency and

service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service

life of aluminum ele

Manufacturer Information

Brand	ldeal
GTIN	00783250300310
UPC	783250300310

Taxonomies, Classifications, and Categories

Category Description	WIRE LUBE, MARKERS, & TIES
Туре	Anti-Oxidant Compound



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging		
Carton	1	
Package	6	
Weight Per each	0.6333	
Uses, Certifications, and Standar	ds	
standard	UL Listed	