

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Availability

minimum qty

301362 Weatherproof Wire Conn, 62 Gray/Red, 1, 000/Box Ideal

Catalog Number	301362
Manufacturer	Ideal
Description	Model 62 Gray-Red 1000 Box
Weight per unit	0.0120 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
ntures	
Quantity	Box of 1000
terial, Color, and Finish	
Color	Gray-Orange
scriptions	
Description	WEATHERPROOF WIRE CONN, 62 GRAY/RED, 1,000/BOX
extra long description	IDEAL 30-1362 WP MODEL 62, GRAY-RED
Features	100% Silicone-based sealant protects against moisture and
	corrosionUL Listed to 486G Sealed Twist-On Wire Connector fo
	use in damp/wet locations or above-grade applicationsEasy to
	apply, pre-filled twist-on wire connectorsSwept wing design is
	built for comfort and efficiencyEliminates the need for
	heat-shrink or excessive tapingTough, UL 94V-2 flame-retardar
	shell rated at 105°C (221°F)For use in damp/wet location or
	above-grade applicationsConnected and protected.Designed
	specifically for above-grade, i
Long Description	MODEL 62 GRAY-RED 1000 BOX
Product Type	WP Model 62, Gray-Red, 1000 BX
Special Features	Hexagonal shape allows connectors to be applied with standar
	nutdriver. Silicone-based sealant protects against moisture an
	corrosion. Easy to apply pre-filled twist-on wire connectors
nufacturer Information	Ideal
Brand	ldeal
GTIN Manufacturors Part Number	00783250756346
Manufacturers Part Number UPC	30-1362 783250756346
conomies, Classifications, and C	
onomies Liassifications and C	ategories
	WIRE NUTS

1000



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1000
Weight Per each	0.012
Uses, Certifications, and Standards	
Application	Handles wire sizes from #18 to #8 AWG copper. Minimum of 2
	#18 AWG Maximum of 3 #10 AWG

UL Listed to 486D for use with damp/wet locations