

Insulated Diagonal Cutters



 1000volt

WH328 Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,  up to 1000 volt. Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 60 HRC. Special tool steel hardened and tempered. For soft & medium hard wire. 32832 & 32834 for soft, hard & piano wire.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Copper AWG	Pkg.	wt.	
WH32830	140	5.5	#6	1	.47	
WH32832	160	6.3	#6	1	.49	
WH32834	180	7.0	#6	1	.62	

Insulated High Leverage Diagonal Cutters



New dynamic joint provides 40% easier cuts and significantly longer tool life

 1000volt

WH328 High Leverage Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,  up to 1000 volt. Individually Tested. DIN ISO 5749 Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64 HRC. C 60 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Copper AWG	Pkg.	wt.	
WH32835	160	6.3	#6	1	.64	
WH32836	180	7.0	#5	1	.67	
WH32838	200	8.0	#4	1	.80	

Insulated Electrician's Diagonal Cutters

Strips AWG #10 & #14



 1000volt

WH32861 Diagonal Cutters W/Stripping Holes. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,  up to 1000 volt. Individually Tested. Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60 HRC), chrome-nickel plated, mirror-polished. Ergo comfort grip with slip guard. Holes in the cutting edge for stripping copper wire of Ø 1.5 and 2.5.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Copper AWG	Pkg.	wt.	
WH32861	160	6.3	#6	1	.55	

Insulated Serrated Edge Cable Cutters



 1000volt

WH328 Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA,  up to 1000 Volt. Individually Tested. Light, clean cutting ground precision cutting edges. Durable cutting is achieved through additional inductive hardening to approx. 62 HRC. Special tool steel, hardened & tempered. For cutting of copper & aluminum cables without crushing.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Ø	mm2	Pkg.	lbs.
WH32826	160	6.3	16	50	1	.42
WH32828	200	8.0	20	60	1	.67

Insulated Crimping Pliers



NEW
From Wiha



WH32841 Insulated Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA,  up to 1000 Volt. Individually Tested.

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64 HRC. CV 60 special tool steel hardened & tempered.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	mm2	AWG	Pkg.	wt.
WH32841	180	7.0	0.25-2.5	6-30	1	.57

Insulated Diagonal Cutters



 1000volt

WH328 Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,  up to 1000 volt. Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 60 HRC. Special tool steel hardened and tempered. For soft & medium hard wire. 32832 & 32834 for soft, hard & piano wire.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Copper AWG	Pkg.	wt.	
WH32830	140	5.5	#6	1	.47	
WH32832	160	6.3	#6	1	.49	
WH32834	180	7.0	#6	1	.62	

Insulated High Leverage Diagonal Cutters



New dynamic joint provides 40% easier cuts and significantly longer tool life

 1000volt

WH328 High Leverage Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,  up to 1000 volt. Individually Tested. DIN ISO 5749 Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64 HRC. C 60 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Copper AWG	Pkg.	wt.	
WH32835	160	6.3	#6	1	.64	
WH32836	180	7.0	#5	1	.67	
WH32838	200	8.0	#4	1	.80	

Insulated Electrician's Diagonal Cutters

Strips AWG #10 & #14



 1000volt

WH32861 Diagonal Cutters W/Stripping Holes. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,  up to 1000 volt. Individually Tested. Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60 HRC), chrome-nickel plated, mirror-polished. Ergo comfort grip with slip guard. Holes in the cutting edge for stripping copper wire of Ø 1.5 and 2.5.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Copper AWG	Pkg.	wt.	
WH32861	160	6.3	#6	1	.55	

Insulated Serrated Edge Cable Cutters



 1000volt

WH328 Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA,  up to 1000 Volt. Individually Tested. Light, clean cutting ground precision cutting edges. Durable cutting is achieved through additional inductive hardening to approx. 62 HRC. Special tool steel, hardened & tempered. For cutting of copper & aluminum cables without crushing.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	Ø	mm2	Pkg.	lbs.
WH32826	160	6.3	16	50	1	.42
WH32828	200	8.0	20	60	1	.67

Insulated Crimping Pliers



NEW
From Wiha



WH32841 Insulated Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA,  up to 1000 Volt. Individually Tested.

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64 HRC. CV 60 special tool steel hardened & tempered.

Item	↔ ↔		Cutting Capacity		⊞	↕ ↕
No.	mm	Inch	mm2	AWG	Pkg.	wt.
WH32841	180	7.0	0.25-2.5	6-30	1	.57