

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



5021M 105-130V 1200W, Mov, Delayed Response, Turnlock *Nsi Industries*

3000	
Catalog Number	5021M
Manufacturer	Nsi Industries
Description	Delayed Response Utility, 105 to 130 V Ac, 1200 W, 3.187 In Width, 2.187 In Height, Lexan Housing Material, Gray, Cadmium Coated CDS Photocell Sensor, -40 °F Operating Temperature, +140 °F Operating Temperature, Twist Lock Mount, 0.2 LB/Ea
Weight per unit	0.2000 (lbs/each)
Product Category	Lighting Photocells
Features	
supply voltage	105-130 VAC
Timing Range	2 Minutes
Dimensions and Weight	
Size	H=2.187 - W=3.187
Descriptions	
Description	105-130V 1200W, MOV, DELAYED RESPONSE, TURNLOCK
extra long description	TORK 5021M TurnLock Utility 120V .5
Manufacturer Information	
GTIN	00786261610157
UPC	786261610157
Taxonomies, Classifications, and	Categories
Category Description	
Туре	Delayed Response Utility Grade
Packaging	
Carton	1
Weight Per each	0.2
Uses, Certifications, and Standar	rds
Application	Street-Highway Lighting
Enclosure	Lexan Housing
environmental conditions	-40 to + 140 F
Frequency Rating	50-60 Hz
Mounting	TWIST LOCK
Operating Temperature	-40 to + 140 F
standard	cULus