


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





5260GR 4" 90D Ext Bond LT Flex Conn *Abb Installation Products, Inc*

| Catalog Number | 5260GR |
|------------------------------------|--|
| Manufacturer | Abla lastallation Duodusta las |
| Description | 4 Inch 90 Degree Malleable Iron External Bonding Liquidtight |
| | Connector, Non-Insulated |
| Weight per unit | 21.9 (lbs/each) |
| Product Category | Liquid Tight Fittings |
| Features | |
| Material | Malleable Iron |
| Material, Color, and Finish | |
| Finish | Electro Zinc Plated/Chromate Coating |
| Dimensions and Weight | |
| Size | 4 INCH |
| Descriptions | |
| Description | 4" 90D EXT BOND LT FLEX CONN |
| extra long description | ABB 5260GR 4IN 90D LT NONINSUL GRND |
| Long Description | 4 Inch 90 Degree Malleable Iron External Bonding Liquidtight |
| | Connector, Non-insulated |
| Product Type | 4IN 90D LT Noninsul GRND Conn Irn |
| Manufacturer Information | |
| Brand | T&B Ind Fitting |
| GTIN | 00786210896236 |
| Manufacturers Part Number | 5260GR |
| UPC | 786210896236 |
| Taxonomies, Classifications, and C | Categories |
| Category Description | FLEX & MC FITTINGS |
| Туре | Grounding Connectors-90 degree |

Packaging

| Carton | 1 |
|-----------------|-------|
| Weight Per each | 21.91 |

Uses, Certifications, and Standards

| Application | To positively bond conduit to box or enclosure |
|-------------|--|
| standard | UL E3060, CSA |