

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Weight Per each

5333GR 3/4" STRT LT Insltd GRND Conn *Abb Installation Products, Inc*

Catalog Number	5333GR
Manufacturer	Abb Installation Products, Inc
Description	3/4 Inch Steel External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, Straight, With Revolver Lug, With Tin Plated Copper Alloy Lug For Awg #14 to #2 Ground Wire, For Use In Wet Locations, 25 Pieces
Weight per unit	0.2600 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
Material	Steel
Material, Color, and Finish	
Finish	Electro Zinc Plated/Chromate Coating
Dimensions and Weight	
Size	3/4 INCH
Descriptions	
Description	3/4" STRT LT INSLTD GRND CONN
extra long description	ABB 5333GR 3/4 INSUL GRND LIQUIDTIG
Long Description	3/4 Inch Steel External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, Straight, With Revolver Lug, With Tin Plated Copper Alloy Lug for Awg #14 to #2 Ground Wire, for Use In Wet Locations, 25 Pieces
Product Type	3/4 Insul GRND Liquidtight Straight
Manufacturer Information	
Brand	T&B Ind Fitting
GTIN	00786210899992
Manufacturers Part Number	5333GR
UPC	786210899992
Taxonomies, Classifications, and C	Categories
Category Description	NACTALLIC CITTINGS
Туре	Grounding Connectors-Straight
Packaging	
Carton	25

0.26

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	To positively bond conduit to box or enclosure
standard	UL E3060, CSA