

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Width

## **5362WSP TVSS Recp 20A 125V Alarm WH** Pass & Seymour/Legrand

Catalog Number	5362WSP
Manufacturer	Pass & Seymour/Legrand
Description	Surge Protective Extra Heavy-Duty Duplex Receptacle Offers Increased Transient Protection, Reliability and Protection Notification (Audible Alarm With Led Indicator). Back and, Side Wire, 20AMP 125VOLT, White.
Weight per unit	0.3712 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
Features	
amperage rating	20
connection	Back and side wire
Material	Nylon
media	Yes
Number of Wires	3
Poles	2
Voltage Rating	125
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	#14 #10
Material, Color, and Finish	
Color	White
Finish	Matte
Dimensions and Weight	
Height	3.75

1.25



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

				•	
ı١	esc	١'n	nt	ın	nc
v	ころし	, I I	IJι	IU	1112

TVSS RECP 20A 125V ALARM WH
P&S 5362WSP TVSS RECP 20A 125V ALAR
Surge Protective Extra Heavy-Duty Duplex Receptacle offers increased transient protection, reliability and protection notification (Audible Alarm with LED Indicator). Back and, Side Wire, 20amp 125volt, White.
TVSS Recp 20A 125V Alarm WH
Solid-state LED monitor has 25-year minimum life expectancy. A high visibility, wide-angle lens indicates protection is in place. LED Indication: steady green = protected, flashing red = not protected, OFF = no power to unit. Audible alarm alert of MOV damage. Alarm able to be turned On/Off. Wrap-around steel strap for structural integrity. Auto-ground is standard, for easier installation. Impact-resistant nylon exterior resists impacts and scrapes. Triple-wipe, copper-alloy contacts for superior, more dep

#### **Manufacturer Information**

Brand	Pass and Seymour
GTIN	00785007193442
Manufacturers Part Number	5362-WSP
UPC	785007193442

#### **Taxonomies, Classifications, and Categories**

Category Description	Commercial receptacles
Туре	Spec Grade Surge Protective Receptacle, Audible Alarm with LED
	Indicator
Trade Size	
Amperage	20.0

### Amperage

Packaging		
Carton	10	
Package	50	
Weight Per each	0.3712	



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

#### **Uses, Certifications, and Standards**

Application	Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
nema rating	5-20R
standard	cULus
Temperature Rating	Operating Temperature: -20°C to +55°C (-4°F to 131°F), Storage Temperature: -40°C to +85°C (-40°F to 185°F)