

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Uses, Certifications, and Standards

standard

562BULK Scotchlok Electrical Idc, YI, 12awg *Minnesota Minina (3M)*

Minnesota Mining (3M)	
Catalog Number	562BULK
Manufacturer	Minnesota Mining (3M)
Description	3M™ Scotchlok™ Insulation Displacement Connector 562 Is A Double Run or Tap Connector For Tap or Parallel Splicing. Polypropylene Insulated, Self Stripping and Flame Retardant.
Weight per unit	7.4 (lbs/each)
Product Category	Small Terminals & Connectors
Descriptions	
extra long description	3M 7100003124 3M™ Scotchlok™ IDC C
Features	3M [™] Scotchlok [™] Insulation Displacement Connector 562 is 600V rated for building wire and 1000V rated for signs, fixtures and luminaires. It withstands temperatures of 194 degrees F (90 degrees C). UL Listed and RoHS 2011/65/EU Compliant.
Long Description	3M™ Scotchlok™ Insulation Displacement Connector 562 is a double run or tap connector for tap or parallel splicing. Polypropylene insulated, self stripping and flame retardant.
Product Type	3M™ Scotchlok™ Idc Connector 562
Special Features	Flame Retardant
Manufacturer Information	
Brand	Scotchlok
GTIN	00054007110408
Manufacturers Part Number	7100003124
UPC	054007110408
Taxonomies, Classifications, and Category Description	
Type	
,	insulation displacement
Packaging Carton	500
Package	5000
Weight Per each	7.4

UL