

Bulb Shape	Base	Watts	Order Code	Description	Volts	Case Qty	Filament Design	MOL (in)	LCL (in)	Rated Life (hrs)	Lumens Initial	Color Temp K	CBCP	Beam Spread	Warning and Caution Notices	Reduced Wattage	Additional Information
Decorative (continued)																	
40 Watts (continued)																	
G16.5	Med	40	31109	40GM/CL-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		Clear, Globe, Medium Base, BDTH
		40	31110	40GM/W-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		White, Globe, Medium Base, BDTH
G25	Med	40	12979	40G25/W 6PK	120	6	CC-6	4.50		1500							White, Globe
		40	12980	40G25 6PK	120	6	CC-6	4.50		1500							Clear, Globe
		40	48694	40G25C/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®
G40	Med	40	48695	40G25W/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®
		40	36191	40G40/W 6PK	120	6	CC-6	6.93		2500							White, Globe
60 Watts																	
B10	Cand	60	27298	60BC/CD4	120	30	CC-2V	3.75		1500							Clear, Blunt Tip
		60	74036	60BC/RVL/CF-T4/6	120	6	C-7A	3.75		1500							Reveal® Clear, Ceiling Fan, Blunt Tip
B13	Med	60	27497	60BM/CD4	120	6	C-9	4.62		1500							Clear, Blunt Tip
		60	72781	60BM/RVL/CD2-4PK	120	4	C-9	4.62		1500				2c, 9i		Reveal®, Blunt Tip	
CA10	Med	60	21009	60CAM CARD4	120	30	CC-2V	4.56		1500							Clear, Bent Tip
CA10	Cand	60	15781	60CAC 25PK	120	200	CC-2V	4.12		1500							Clear, Bent Tip
		60	16050	60CAC CARD 4	120	30	CC-2V	4.12		1500							Clear, Bent Tip
		60	16051	60CAC/F CARD4	120	30	CC-2V	4.12		1500							Frost, Bent Tip
G16.5	Cand	60	72777	60GC/CD2-4PK	120	4	CC-2V	3.00		1500				5e, 9d		Clear, Globe	
G16.5	Cand	60	44723	60GC/W PQ2/6	120	30	CC-2V	3.00		1500				5e, 9d		White, Globe	
G16.5	Med	60	31114	60GM/CL-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		Clear, Globe, Medium Base, BDTH
		60	31115	60GM/W-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		White, Globe, Medium Base, BDTH
G25	Med	60	42360	60G25C/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®, Clear-Globe
		60	42361	60G25W/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®, White - Globe
		60	14846	60G25 6PK	120	6	CC-6	4.50		1500							Clear, Globe
		60	14848	60G25/W 6PK	120	6	CC-6	4.50		1500							White - Globe
G30	Med	60	14850	60G30/W 6PK	120	24	CC-9	5.00		2500							White - Globe, Retail Pack
G40	Med	60	14187	60G40 6PK	120	6	CC-6	6.93		2500							Clear - Globe
		60	49780	60G40/W 6PK	120	6	CC-6	6.93		2500							White - Globe
75 Watts																	
E17	Med	75	73289	75E17/TF-4PK	120	4	CC-6	5.00		4000							
G40	Med	75	36193	75G40/W 6PK	120	6	CC-6	6.93		2500							White - Globe
100 Watts																	
F20	Med	100	44540	100F20/TF PQ1/6	120	30	CC-9	5.00		3000							Post Light, Teflon® Coated, Saf-T-Gard® BB
G40	Med	100	16742	100G40/W CPK	120	24	CC-6	6.93		2500							White - Globe
		100	49781	100G40/W 6PK	120	6	CC-6	6.93		2500							White - Globe
150 Watts																	
G40	Med	150	16585	150G40/W	120	24	CC-6	6.93		2500							White - Globe
Portable Lighting Products																	
R30	Med	65	44848	PLK 1 UNIT	120	4	CC-6	5.37		2000					2a, 5e, 9k		Plant Light Kit includes one 75R30/PL Plant Light lamp, UL listed holder and information booklet.

Bulb Shape	Base	Watts	Order Code	Description	Volts	Case Qty	Filament Design	MOL (in)	LCL (in)	Rated Life (hrs)	Lumens Initial	Color Temp K	CBCP	Beam Spread	Warning and Caution Notices	Reduced Wattage	Additional Information
Decorative (continued)																	
40 Watts (continued)																	
G16.5	Med	40	31109	40GM/CL-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		Clear, Globe, Medium Base, BDTH
		40	31110	40GM/W-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		White, Globe, Medium Base, BDTH
G25	Med	40	12979	40G25/W 6PK	120	6	CC-6	4.50		1500							White, Globe
		40	12980	40G25 6PK	120	6	CC-6	4.50		1500							Clear, Globe
		40	48694	40G25C/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®
G40	Med	40	48695	40G25W/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®
		40	36191	40G40/W 6PK	120	6	CC-6	6.93		2500							White, Globe
60 Watts																	
B10	Cand	60	27298	60BC/CD4	120	30	CC-2V	3.75		1500							Clear, Blunt Tip
		60	74036	60BC/RVL/CF-T4/6	120	6	C-7A	3.75		1500							Reveal® Clear, Ceiling Fan, Blunt Tip
B13	Med	60	27497	60BM/CD4	120	6	C-9	4.62		1500							Clear, Blunt Tip
		60	72781	60BM/RVL/CD2-4PK	120	4	C-9	4.62		1500				2c, 9i		Reveal®, Blunt Tip	
CA10	Med	60	21009	60CAM CARD4	120	30	CC-2V	4.56		1500							Clear, Bent Tip
CA10	Cand	60	15781	60CAC 25PK	120	200	CC-2V	4.12		1500							Clear, Bent Tip
		60	16050	60CAC CARD 4	120	30	CC-2V	4.12		1500							Clear, Bent Tip
		60	16051	60CAC/F CARD4	120	30	CC-2V	4.12		1500							Frost, Bent Tip
G16.5	Cand	60	72777	60GC/CD2-4PK	120	4	CC-2V	3.00		1500				5e, 9d		Clear, Globe	
G16.5	Cand	60	44723	60GC/W PQ2/6	120	30	CC-2V	3.00		1500				5e, 9d		White, Globe	
G16.5	Med	60	31114	60GM/CL-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		Clear, Globe, Medium Base, BDTH
		60	31115	60GM/W-PQ2/6	120	30	CC-2V	3.00		1500					5e, 9d		White, Globe, Medium Base, BDTH
G25	Med	60	42360	60G25C/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®, Clear-Globe
		60	42361	60G25W/RVL PQ1/6	120	6	CC-6	4.50		1500							Reveal®, White - Globe
		60	14846	60G25 6PK	120	6	CC-6	4.50		1500							Clear, Globe
		60	14848	60G25/W 6PK	120	6	CC-6	4.50		1500							White - Globe
G30	Med	60	14850	60G30/W 6PK	120	24	CC-9	5.00		2500							White - Globe, Retail Pack
G40	Med	60	14187	60G40 6PK	120	6	CC-6	6.93		2500							Clear - Globe
		60	49780	60G40/W 6PK	120	6	CC-6	6.93		2500							White - Globe
75 Watts																	
E17	Med	75	73289	75E17/TF-4PK	120	4	CC-6	5.00		4000							
G40	Med	75	36193	75G40/W 6PK	120	6	CC-6	6.93		2500							White - Globe
100 Watts																	
F20	Med	100	44540	100F20/TF PQ1/6	120	30	CC-9	5.00		3000							Post Light, Teflon® Coated, Saf-T-Gard® BB
G40	Med	100	16742	100G40/W CPK	120	24	CC-6	6.93		2500							White - Globe
		100	49781	100G40/W 6PK	120	6	CC-6	6.93		2500							White - Globe
150 Watts																	
G40	Med	150	16585	150G40/W	120	24	CC-6	6.93		2500							White - Globe
Portable Lighting Products																	
R30	Med	65	44848	PLK 1 UNIT	120	4	CC-6	5.37		2000					2a, 5e, 9k		Plant Light Kit includes one 75R30/PL Plant Light lamp, UL listed holder and information booklet.