

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **65216 Led DBL Head Security Flood White No MS** *Satco*

Catalog Number	65216
Manufacturer	Satco
Description	Led Security Light - Dual Head White Finish 4000K
Weight per unit	2.5 (lbs/each)
Product Category	Security Lights
eatures	
amperage rating	0.200 to 0.072
Ballast Type	Self
Lamp Type	LED
Material	Die Cast Aluminum
Number of Lamps	2
Power Rating	0.9
Reflector Type	
Socket Type	Integrated
Voltage Rating	120 to 277
Warranty	5 Year Limited - Fixtures
Wattage	20
Material, Color, and Finish	
fixture material	die-cast aluminum
Style	Utility
imensions and Weight	
Height	7.63
Length	7.63
Size	L:7.63 W:4.16 H:4.13
Width	4.16
escriptions	
Description	LED DBL HEAD SECURITY FLOOD WHITE NO MS
extra long description	SATCO 65/216 LED DUAL HEAD SECURITY
Long Description	LED Security Light - Dual Head White Finish 4000K
Product Type	Led Dual Head Security Light
Special Features	Warranty: 5-Years ; FCC Compliant: True ; Cct Selectable: False CCT (Kelvin Temp): 4000K ; Hours Rated: 50000 ; Beam Angle
	(1 ) 50 1 1 0 11 0 11 15 5 15 15 15

(degree): 50; Indoor Outdoor: Outdoor; IP Rating: IP65; Lens Finish: Frost; Lens Material: Glass; Operating Temp: -30C (-22F)

to +50C (+122F); Watts: 20W; Lumens: 1900L



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				<b>.</b>					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	<b>7</b>
	v			u	а	L.I	uı	<b>CI</b>	'In	H.V.	,, ,	па		u	

Brand	Nuvo
GTIN	00045923680403
Manufacturers Part Number	65/216
UPC	045923680403

#### **Taxonomies, Classifications, and Categories**

Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE
	LIGHTING
Туре	Commercial LED

#### **Packaging**

Carton 1 Weight 2.54	onaging		
	Carton	1	
#18.1 in the state of the state	Weight	2.54	
Weight Per each 2.54		2.54	

#### Uses, Certifications, and Standards

Application	Outdoor
environmental conditions	Wet
Frequency Rating	50/60
	-30C (-22F) to a maximum of +50C (+122F)
standard	cULus - Certified