

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### 670GSA 2" Alu FM7 Cond CVR/Gasket Crouse-Hinds

<b>国题题《人》</b>	
Catalog Number	670GSA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 7 Cover With Integral
	Gasket, Sheet Aluminum, 2"
Weight per unit	0.0300 (lbs/each)
Product Category	Alum
eatures	
dimensions	3.6000 IN X 3.2600 IN X 1.5100 IN
Material	Aluminum
Dimensions and Weight	
Height	1.51
Length	3.6
Width	3.26
Descriptions	
Description	2" ALU FM7 COND CVR/GASKET
extra long description	CRS-H 670G SA 2 WDGNUT SHT AL FORM
Features	One hundred years after the introduction of the Condulet, Eator remains the leader in conduit outlet bodies with its Crouse-Hind series. The line has grown to six families manufactured in a variety of materials, and Form 7 bodies are offered in 11 different shapes to provide the most flexible offering on the market. Form 7 Condulet outlet bodies approach conduit in size for neat, compact installations. Many shapes and sizes are available for rigid threaded conduit. Our Form 7 family features an exclus
Long Description	Eaton Crouse-Hinds series Condulet Form 7 cover with integral gasket, Sheet aluminum, 2"
Product Type	2 Wdgnut SHT Al Form 7 CVR/Gask
Special Features	With Neoprene Integral Gasket
/Janufacturer Information	
Brand	Eaton
GTIN	00782274247953
Manufacturers Part Number	670G SA

### **Taxonomies, Classifications, and Categories**

**UPC** 

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Cover with integral gasket

782274247953



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

				•	
110	$\Delta \mathbf{I}$	<i>,</i> ~	$\sim$	110	•
Pa	( . R				Ш
·	v	١u	м		•

Carton	1	
Package	10	
Weight Per each	0.03	

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D