

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### 670LAG Combo 2 Switches 1P 20A 120/277V La

Pass & Seymour/Legrand

Catalog Number	670LAG
Manufacturer	Pass & Seymour/Legrand
Description	Single-Pole, Double Combination Switch, 20A, 120/277V, White.
Weight per unit	0.2160 (lbs/each)
Product Category	Combination Devices

#### **Features**

itures	(0) 00
action	(2) SP
actuator	Toggle
amperage rating	20
connection	Side wire
Contact Configuration	N-O
Contact Rating	20Amp, 120/277Vac
operating cycles	30000
Poles	Single Pole
Voltage	0.433 V
Voltage Rating	0.433212996389892
Wattage	Electrical power is expressed in Amps and Volts.

#### **Dimensions and Weight**

•	
Cizo	1 22 1 0 04 1 1 4 0 / 1 1
SIZE	1.32 L x 0.94 W x 4.06 H
JILO	1.02 L X 0.7 I VV X 1.00 II

#### **Descriptions**

Description	COMBO 2 SWITCHES TP 20A 120/277V LA
extra long description	P&S 670LAG COMBO 2 SWITCHES 1P 20A
Long Description	Single-Pole, Double Combination Switch, 20A, 120/277V, White.
Product Type	Combo 2 Switches 1P 20A 120/277V La
Special Features	Easily accessible break-off for separate or common feed. Side wire #12 and #14 AWG. Two devices fit into the space of one.
	Grounding combination devices meet NEC Requirements.

#### **Manufacturer Information**

Brand	Pass and Seymour
GTIN	00785007006032
Manufacturers Part Number	670LAG
UPC	785007006032

#### **Taxonomies, Classifications, and Categories**

Category Description	Residential Switches
Туре	COMBINATION

#### **Trade Size**

Amperage 20.0	
---------------	--



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kag	ın	g

Carton	10	
Package	50	
Weight Per each	0.216	

### Uses, Certifications, and Standards

Application	Residential/Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
Operating Temperature	Maximum continuous +60°C, minimum -30°C
standard	CULUS, UL20