



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



7023AL 3" Rigid Alu Conduit Strap

Abb Installation Products, Inc

| | |
|------------------|--|
| Catalog Number | 7023AL |
| Manufacturer | Abb Installation Products, Inc |
| Description | Strap, 12 Gauge, Size 3 Inch, Outer Diameter Size 3.500 Inches, Aluminum, For Rigid or Imc Conduit, Pipe and Electrical Metal Tubing |
| Weight per unit | 0.1850 (lbs/each) |
| Product Category | Channel & Strut Fittings |

Features

| | |
|----------|-------|
| Material | Steel |
|----------|-------|

Dimensions and Weight

| | |
|------|----------|
| Size | 3 Inches |
|------|----------|

Descriptions

| | |
|------------------------|--|
| Also Known As... | Strut Strap Pipe Clamp for Strut Conduit/Pipe Clamp for Strut Strut Clamp |
| Description | 3" RIGID ALU CONDUIT STRAP |
| extra long description | ABB 702 3 AL RGD COND CLP 3IN 12GA |
| Long Description | Strap, 12 Gauge, Size 3 Inch, Outer Diameter Size 3.500 Inches, Aluminum, For Rigid or IMC Conduit, Pipe and Electrical Metal Tubing |
| Product Type | RGD Cond CLP 3IN 12GA Aluminum |
| Special Features | Bolt head is combination slot and hex head for flexibility of attachment |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Superstrut |
| GTIN | 00616013141274 |
| Manufacturers Part Number | 702 3 AL |
| UPC | 616013141274 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | STRUT STRAPS |
| Type | Pipe Straps, Pipe Clamps & Hangers (Series 700) |

Packaging

| | |
|-----------------|-------|
| Carton | 25 |
| Weight Per each | 0.185 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Superstrut Pipe Straps are Designed to be Twist Inserted
Anywhere Along the Slot Side of the Channel
