

# ETP Raintight 700GSR Series Gland Compression Connectors

## Application

- To ground and secure EMT raceway to boxes and enclosures in wet conditions.

## Features

- UL Listed Raintight.
- Green compression nut identifies the fitting as raintight.
- No disassembly required.
- Male hub threads NPS.
- Available with and without insulated throat.
- Concretetight.

## Materials/Finish

- Body and nut: steel
- Knockout sealing ring: EPDM rubber
- Body and nut: zinc electroplate

## Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- UL Listed Raintight



7100GSR



7100GSRT

| Trade Size<br>(Inches) | Dimensions in Millimeters (Inches) |                     |                  |  | Weight per 100<br>kg (lb) | Catalog Number              |                  |
|------------------------|------------------------------------|---------------------|------------------|--|---------------------------|-----------------------------|------------------|
|                        | Body<br>Length                     | Maximum<br>Diameter | Thread<br>Length |  |                           | Without<br>Insulated Throat | Insulated Throat |
| 1/2                    | 36.6 (1.44)                        | 27.9 (1.10)         | 8.6 (0.34)       |  | 4.5 (10)                  | 7050GSR                     | 7050GSRT         |
| 3/4                    | 38.1 (1.50)                        | 34.5 (1.36)         | 8.6 (0.34)       |  | 6.8 (15)                  | 7075GSR                     | 7075GSRT         |
| 1                      | 44.5 (1.75)                        | 34.5 (1.36)         | 9.9 (0.39)       |  | 10.0 (22)                 | 7100GSR                     | 7100GSRT         |
| 1-1/4                  | 50.8 (2.00)                        | 52.6 (2.07)         | 10.2 (0.40)      |  | 16.3 (36)                 | 7125GSR                     | 7125GSRT         |
| 1-1/2                  | 50.8 (2.00)                        | 58.7 (2.31)         | 10.2 (0.40)      |  | 18.1 (40)                 | 7150GSR                     | 7150GSRT         |
| 2                      | 58.9 (2.32)                        | 70.9 (2.79)         | 10.4 (0.41)      |  | 24.5 (54)                 | 7200GSR                     | 7200GSRT         |
| 2-1/2                  | 91.9 (3.62)                        | 92.2 (3.63)         | 16.5 (0.65)      |  | 68.0 (150)                | 7250GSR                     | 7250GSRT         |
| 3                      | 95.3 (3.75)                        | 109.0 (4.29)        | 16.5 (0.65)      |  | 83.9 (185)                | 7300GSR                     | 7300GSRT         |
| 3-1/2                  | 97.8 (3.85)                        | 121.9 (4.80)        | 18.3 (0.72)      |  | 97.5 (215)                | 7350GSR                     | 7350GSRT         |
| 4                      | 99.1 (3.90)                        | 133.9 (5.27)        | 18.3 (0.72)      |  | 108.0 (238)               | 7400GSR                     | 7400GSRT         |

# ETP Raintight 700GSR Series Gland Compression Connectors

## Application

- To ground and secure EMT raceway to boxes and enclosures in wet conditions.

## Features

- UL Listed Raintight.
- Green compression nut identifies the fitting as raintight.
- No disassembly required.
- Male hub threads NPS.
- Available with and without insulated throat.
- Concretetight.

## Materials/Finish

- Body and nut: steel
- Knockout sealing ring: EPDM rubber
- Body and nut: zinc electroplate

## Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- UL Listed Raintight



7100GSR



7100GSRT

| Trade Size<br>(Inches) | Dimensions in Millimeters (Inches) |                     |                  |                             | Weight per 100<br>kg (lb) | Catalog Number   |  |
|------------------------|------------------------------------|---------------------|------------------|-----------------------------|---------------------------|------------------|--|
|                        | Body<br>Length                     | Maximum<br>Diameter | Thread<br>Length | Without<br>Insulated Throat |                           | Insulated Throat |  |
| 1/2                    | 36.6 (1.44)                        | 27.9 (1.10)         | 8.6 (0.34)       | 4.5 (10)                    | 7050GSR                   | 7050GSRT         |  |
| 3/4                    | 38.1 (1.50)                        | 34.5 (1.36)         | 8.6 (0.34)       | 6.8 (15)                    | 7075GSR                   | 7075GSRT         |  |
| 1                      | 44.5 (1.75)                        | 34.5 (1.36)         | 9.9 (0.39)       | 10.0 (22)                   | 7100GSR                   | 7100GSRT         |  |
| 1-1/4                  | 50.8 (2.00)                        | 52.6 (2.07)         | 10.2 (0.40)      | 16.3 (36)                   | 7125GSR                   | 7125GSRT         |  |
| 1-1/2                  | 50.8 (2.00)                        | 58.7 (2.31)         | 10.2 (0.40)      | 18.1 (40)                   | 7150GSR                   | 7150GSRT         |  |
| 2                      | 58.9 (2.32)                        | 70.9 (2.79)         | 10.4 (0.41)      | 24.5 (54)                   | 7200GSR                   | 7200GSRT         |  |
| 2-1/2                  | 91.9 (3.62)                        | 92.2 (3.63)         | 16.5 (0.65)      | 68.0 (150)                  | 7250GSR                   | 7250GSRT         |  |
| 3                      | 95.3 (3.75)                        | 109.0 (4.29)        | 16.5 (0.65)      | 83.9 (185)                  | 7300GSR                   | 7300GSRT         |  |
| 3-1/2                  | 97.8 (3.85)                        | 121.9 (4.80)        | 18.3 (0.72)      | 97.5 (215)                  | 7350GSR                   | 7350GSRT         |  |
| 4                      | 99.1 (3.90)                        | 133.9 (5.27)        | 18.3 (0.72)      | 108.0 (238)                 | 7400GSR                   | 7400GSRT         |  |