


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





7620T95 Cold Shrink Qtiii Term Kit 7620-T-95 *Minnesota Mining (3M)*

Catalog Number	7620T95
Manufacturer	Minnesota Mining (3M)
Description	3M™ Cold Shrink QT-lii Silicone Rubber Termination Kit 7620-T and 7690-T Series Contains One-Piece, Non-Skirted, Silicone Rubber Terminations, Meets Ieee Standard 48 Class 1 For Indoor and Weather-Protected Applications. The Kits Are Designed For Terminating Solid Dielectric Shielded Power Cable Rated 5–35 KV With Tape Shield, Wire Shield and Unishield® Constructions.
Weight per unit	•
Product Category	Splicing & Terminating Kits
escriptions	
Description	COLD SHRINK QTIII TERM KIT 7620-T-95
extra long description	3M 7000006100 3M™ Cold Shrink QT-II
Features	Each kit contains sufficient quantities of material to make three single-phase terminations. The termination assemblies consist of a tubular insulator, high dielectric constant (Hi-K) stress control tube, conformable Hi-K stress controlling compound, and built-in environmental top seal. The insulator is made of a dark gray silicone rubber with advanced tracking resistant and hydrophobi properties. Note:Lugs need to be ordered separately. Exceptions:For T-150 Kits, 150 kV impulse level meets the impulse r
Long Description	3M™ Cold Shrink QT-III Silicone Rubber Termination Kit 7620-T and 7690-T Series contains one-piece, non-skirted, silicone rubber terminations, meets IEEE Standard 48 Class 1 for indoor and weather-protected applications. The kits are designed for terminating solid dielectric shielded power cable rated 5–35 kV, with tape shield, wire shield and UniShield® constructions.
Product Type	3M™ Cold Shrink QT-Iii Termination Kit 7620-T & 7690-T Serie
anufacturer Information	
Brand	3M
GTIN	00054007417583
Manufacturers Part Number	
UPC	
exonomies, Classifications, and (
	HEAT/COLD SHRINK
Туре	QT-III



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging		
Carton	1	
Weight Per each	2.56	
Uses, Certifications, and Standard	s	
Application	Indoor	
standard	IEEE	