



INDUSTRIAL  
COMMERCIAL  
RESIDENTIAL

## V-9 ELECTRICAL ACCESSORIES

### MATERIAL CHARACTERISTICS

Cat. No.'s 87 & 88

Environmental:

Flammability  
per UL 94  
requirements,  
V2 rated.

Temperature Rating:  
-40°C to 80°C.

Bushings:

Meets flammability  
requirements per  
UL 94, VO rated.

Temperature Rating:

76 and 77:

-20°C to 70°C,

28 and 30:

-20°C to 60°C.



2529C



2530



7949



756



76



28

## Miscellaneous Accessories

### Plate Screws and Key

#### FEATURES

- All screws are #6-32.

#### Spanner Head

| Description      | Finish   | Length               | Catalog No. |
|------------------|----------|----------------------|-------------|
| Tamper resistant | Chromium | 13/32"<br>(10.319mm) | 2529C       |
| Key for 2529C    | —        |                      | 2530        |

### Metal Switch Lever Guard

#### FEATURES

- Nickel finish
- For flush tumbler switch levers
- Attaches to standard plates by the plate screws

#### Metal Switch Lever Guard

| Description                               | Catalog No. |
|---|-------------|
| Switch lever guard with 1/4 padlock holes | 7949        |

#### Sub-Frame and Blank Insert

| Description                                      | Color        | Catalog No. |
|--|--------------|-------------|
| Blank insert and strap for standard switch plate | Brown        | 756B        |
|  | Gray         | 756GY       |
|  | Ivory        | 756V        |
|  | Light Almond | 756LA       |
|  | White        | 756W        |

### Bushings

#### FEATURES

- Provide smooth protective surface for cords or wires passing through knockouts.

#### Bushings

| Description           | Knockout Size       | Inside Diameter     | Outside Diameter    | Groove               | Catalog No. |
|-----------------------|---------------------|---------------------|---------------------|----------------------|-------------|
| Rubber                | 0.375"<br>(9.525mm) | 0.375"<br>(9.525mm) | 0.75"<br>(19.05mm)  | 0.50"<br>(12.70mm)   | 76          |
| Rubber                | 0.50"<br>(12.70mm)  | 0.50"<br>(12.70mm)  | 1.031"<br>(26.19mm) | 0.875"<br>(22.225mm) | 77          |
| Plastic with Lock Nut | 0.50"<br>(12.70mm)  | 0.50"<br>(12.70mm)  | —                   | —                    | 28          |
| Plastic with Lock Nut | 0.75"<br>(19.05mm)  | 0.75"<br>(19.05mm)  | —                   | —                    | 30          |



INDUSTRIAL  
COMMERCIAL  
RESIDENTIAL

## V-9 ELECTRICAL ACCESSORIES

### MATERIAL CHARACTERISTICS

Cat. No.'s 87 & 88

Environmental:

Flammability

per UL 94

requirements,

V2 rated.

Temperature Rating:

-40°C to 80°C.

Bushings:

Meets flammability

requirements per

UL 94, VO rated.

Temperature Rating:

76 and 77:

-20°C to 70°C,

28 and 30:

-20°C to 60°C.



2529C



2530



7949



756



76



28

## Miscellaneous Accessories

### Plate Screws and Key

#### FEATURES

- All screws are #6-32.

#### Spanner Head

| Description      | Finish   | Length               | Catalog No. |
|------------------|----------|----------------------|-------------|
| Tamper resistant | Chromium | 13/32"<br>(10.319mm) | 2529C       |
| Key for 2529C    | —        |                      | 2530        |

### Metal Switch Lever Guard

#### FEATURES

- Nickel finish
- For flush tumbler switch levers
- Attaches to standard plates by the plate screws

#### Metal Switch Lever Guard

| Description                               | Catalog No. |
|---|-------------|
| Switch lever guard with 1/4 padlock holes | 7949        |

#### Sub-Frame and Blank Insert

| Description                                      | Color        | Catalog No. |
|--|--------------|-------------|
| Blank insert and strap for standard switch plate | Brown        | 756B        |
|  | Gray         | 756GY       |
|  | Ivory        | 756V        |
|  | Light Almond | 756LA       |
|  | White        | 756W        |

### Bushings

#### FEATURES

- Provide smooth protective surface for cords or wires passing through knockouts.

#### Bushings

| Description           | Knockout Size       | Inside Diameter     | Outside Diameter    | Groove               | Catalog No. |
|-----------------------|---------------------|---------------------|---------------------|----------------------|-------------|
| Rubber                | 0.375"<br>(9.525mm) | 0.375"<br>(9.525mm) | 0.75"<br>(19.05mm)  | 0.50"<br>(12.70mm)   | 76          |
| Rubber                | 0.50"<br>(12.70mm)  | 0.50"<br>(12.70mm)  | 1.031"<br>(26.19mm) | 0.875"<br>(22.225mm) | 77          |
| Plastic with Lock Nut | 0.50"<br>(12.70mm)  | 0.50"<br>(12.70mm)  | —                   | —                    | 28          |
| Plastic with Lock Nut | 0.75"<br>(19.05mm)  | 0.75"<br>(19.05mm)  | —                   | —                    | 30          |