

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## 870LA Radiant Switch 1P 15A 120/277V La

Pass & Seymour/Legrand

Catalog Number	870LA
Manufacturer	Pass & Seymour/Legrand
Description	The Perfect Upgrade For Your Basic Light Switch, The Single-Pole
	Switch From The Radiant Registered Collection Provides On/Off
	Control Of A Light or Fixture From A Single Location, While
	Combining Clean Lines and Smooth Paddle Action For A
	Sophisticated Touch. Made Exclusively For Use With Screwless Wall Plates From The Radiant Registered Collection, Sold
	Separately.
Weight per unit	•
Product Category	
Features	
Contact Rating	15 Amp, 120/125 VAC
gang	1
insulation	
Material	
media	Yes
Mounting Type	
Number of Gangs	
Number of Switches	1.0
Poles	1
Switch Type	
Voltage	
Wire Size	#14 - #10 Awg
Material, Color, and Finish	
Finish	Matte
Dimensions and Weight	
Size	4.2 in
Thickness	1.5 in



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
extra long description	P&S TM870LA RADIANT SWITCH 1P 15A 1
Long Description	The perfect upgrade for your basic light switch, the Single-Pole Switch from the radiant Registered Collection provides on/off control of a light or fixture from a single location, while combining clean lines and smooth paddle action for a sophisticated touch. Made exclusively for use with screwless Wall Plates from the radiant Registered Collection, sold separately.
Product Type	Radiant Switch 1P 15A 120/277V La
Special Features	Designer style, smooth quiet paddle action
Manufacturer Information	
Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007245394
Manufacturers Part Number	TM870LA
UPC	785007245394
Taxonomies, Classifications, and G	Categories
Category Description	Residential Switches
Туре	SWITCH
Trade Size	
Amperage	15.0
Packaging	
Carton	10
Package	100
Weight Per each	0.14
Uses, Certifications, and Standard	ls
Application	
Mounting	14/411

CULUS, UL, UL 498, 20