

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Ideal	00410
Catalog Number Manufacturer	
Description	ldeal Barrier Strip, 12 Circuits, 12 Poles, 35 A, 300/600 V, Plastic, +221 °F, 5.540 In Overall Length, 0.937 In Overall Width, 0.748 In Overall Height, 0.19 LB
Weight per unit	0.1900 (lbs/each)
Product Category	Power BLKS & Distribution BLKS
Features	
amperage rating	35
Material	Plastic Housing
Wire Size	22-10
Descriptions	
Description	BARRIER STRIP, 12-CIRCUIT
extra long description	IDEAL 89-612 TERMINAL BLOCK 12 POL
Features	IDEAL Barrier Strips are designed and manufactured to be rugged, reliable, and easy to use. A thermoplastic base and corrosion-resistant screws and hardware provide extended service life.
Special Features	Features: UL Recognized And CUL Rated For 35A, 600V; Recessed Screws And Tubular Contacts; Connect Stripped Un-Terminated Solid Or Stranded Wire; Modular 12 Circuits Can Be Cut Into Smaller Sections; Plastic Housing Is UL Flame Rated To 94V-2; Rated Temperature To 105 Degrees C; Torque Rating Of 7.0 In-Lbs; Recessed Screws And Tubular Contacts Provide Added Safety And Help Prevent Short Circuits; Tubular Contacts Connec Stripped, Un-Terminated Solid Or Stranded Wire Directly To Each Contact Integrated Wir
Manufacturer Information	
Brand	Ideal
GTIN	00783250896127
UPC	783250896127
Taxonomies, Classifications, and (	Categories
Category Description	Datacom Wiring Devices and Accessories
Packaging	
Carton	
Weight Per each	0.19
Uses, Certifications, and Standard	S
standard	C/US UL Listed, RoHS