

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

# 

#### AGC5R 5A 250V 1/4X1-1/4 Rohs Fa Glass Fuse

Bussmann Fuses

Catalog Number	AGC5R
Manufacturer	Bussmann Fuses
Description	Fuse, Fast Acting Fuse Speed, 120/3.6K S Response Time, Ferrule
	End X Ferrule End Connection, 5 A, 250 V Ac, Glass (Body);Brass(
	End Cap) Material, Ferrule Terminal, 1/4 In Diameter, 1-1/4 In
Woight par upit	Overall Length, 0.01 LB
Weight per unit	
Product Category	Small Dimension Fuses
eatures	
amperage rating	
connection	Ferrule End X Ferrule End
dimensions	
Response Time	60 min at 135%, 120 sec at 200%
Dimensions and Weight	
Size	1/4 In Diameter X 1-1/4 In Length
Descriptions	
Description	5A 250V 1/4X1-1/4 ROHS FA GLASS FUSE
extra long description	EFSE AGC-5-R BUSS SMALL DIMENSION F
Features	Fast-acting, glass tube 1/4" x 1-1/4" ferrule fuse designed to UL
	248-14 for overcurrent protection of electronic circuits. Install
	into a Bussmann Series fuse holder, block, or fuse clip, or
	purchase with available axial leads for thru-hole installation.
	Eaton's AGC fast-acting, glass tube 1/4" x 1-1/4" ferrule fuses are
	designed to UL 248-14 for overcurrent protection of electronic
	circuits. Order in cartridge fuse format and install into a
	Bussmann Series fuse holder, block, or fuse clip, or purchase w
Special Features	Interrupt Rating 200 Amp at 250 Vac, 10000 Amp at 125 Vac,
	Material Glass Tube, Nickel Plated Brass Endcap, ROHS Complian
Manufacturer Information	
Brand	Eaton Bussmann series
GTIN	00051712655231
UPC	051712655231
axonomies, Classifications, and	l Categories
Category Description	GLASS FUSES (and ceramic)
Туре	Fast-acting glass tube fuse
Packaging	
Carton	5
Weight Per each	0.01



### Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

#### Uses, Certifications, and Standards

standard

CE Marked, RoHS Compliant