



SignPRO

SIGNPRO MAG SIGN BALLAST (2-4) T12/HO 20-40FT 120V

signPRO magnetic ballasts for T12/HO Rapid Start Fluorescent Lamps deliver the combined benefits of efficient operation, long ballast life, and outstanding reliability. Built to perform under all weather conditions, Philips-Advance's family of signPRO magnetic ballasts offers sign suppliers, manufacturers, and installers a broad range of dependable lighting solutions.

Product data

• General Characteristics

| | |
|--------------------------------|------------------------|
| Lamp Type | T12/HO |
| Number of Lamps | 2-4 piece |
| Input Voltage | 120 V |
| Input Current (Operating) | 4 A |
| Line Frequency | 60 Hz |
| Lamp Footage(for sign ballast) | 20 - 40 FT |
| Ballast Type | Magnetic Fluorescent |
| Base Model | ASB204024BLTP |
| Housing | BL3 |
| Housing Dimensions | 19.19" x 3.44" x 2.69" |
| Housing Material | Metal |
| Suitable for Outdoor use? | Yes |
| Starting Method | Rapid Start |
| Family Name | SignPRO |

• Operating Characteristics

| | |
|---------------------------|--------|
| Automatic restart | Yes |
| Ignition time | 1 s |
| Input Power Gear | 472 W |
| Ballast factor | 0.8 - |
| Ballast Efficacy Factor | 0.17 - |
| Power Factor | 0.984 |
| Lamp Current Crest Factor | 1.7 - |
| Sound Rating | C |
| Max THD | 25 % |

• Wiring Characteristics

| | |
|------------------|---------------|
| Wire Striplength | 0.50/0.375 mm |
| Lamp Connection | Series |
| Wire Gauge | 18AWG |

| | |
|---------------------------------|----------------|
| Wire Length by Color | See data sheet |
| Wire Type | Solid |
| Allowed Wiring Config(Remote) | Yes |
| Allowed Wiring Config(Tandem) | Yes |
| Allowed Wiring Config(Through) | Yes |
| Max Dist. Ball to Lamp(Remote) | 15' |
| Max Dist. Ball to Lamp(Tandem) | Any = 15' |
| Max Dist. Ball to Lamp(Through) | Any = 15' |

• System Chars on driver level

| | |
|------------------|------|
| Rated Lamp Watts | 110W |
|------------------|------|

• Product Dimensions

| | |
|-----------|----------|
| Length A1 | 19.19 in |
| Length A2 | 18.63 in |
| Width B1 | 3.19 in |
| Height C1 | 2.63 in |

• Approval & Application Chars

| | |
|-------------------|------------------|
| EMC Immunity | FCC Non-Consumer |
| Approbation Marks | UL, CSA, RoHS |
| UL Listed | Yes |
| CSA certificate | Yes |
| CEC Listing | No |
| Circle E logo | No |
| CSA E | No |
| cUL certificate | No |

PHILIPS


| | |
|------------------|-----|
| DOE | No |
| FIDE Certificate | No |
| NOM certificate | No |
| RoHS Compliant | Yes |
| SASO Certificate | No |
| UL Recognized | No |

| | |
|--------------------|---|
| Short product name | SIGN BALLAST (2-4) T12/HO 20-40FT 120V |
| Pieces per Sku | 1 |
| eop_pck_cfg | 1 |
| Skus/Case | 1 |
| Bar code on pack | 781087000106 |
| Bar code on case | 30781087000107 |
| Logistics code(s) | 913700586409 |
| eop_net_weight_pp | 9.013 kg |

• Product Data


| | |
|-------------------|---|
| Product number | ASB204024BLTPI |
| Full product name | SIGN BALLAST (2-4) T12/HO 20-40FT 120V |

Dimensional drawing



SIGNPRO MAG SIGN BALLAST (2-4) T12/HO 20-40FT 120V

| Product | A1 (Norm) | A2 (Norm) | B1 (Norm) | C1 (Norm) | D1 (Norm) |
|---|-----------|-----------|-----------|-----------|-----------|
| SIGN BALLAST (2-4) T12/HO 20-40FT 120V | 19.19 | 18.63 | 3.19 | 2.63 | - |




© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, February 1
data subject to change



SignPRO

SIGNPRO MAG SIGN BALLAST (2-4) T12/HO 20-40FT 120V

signPRO magnetic ballasts for T12/HO Rapid Start Fluorescent Lamps deliver the combined benefits of efficient operation, long ballast life, and outstanding reliability. Built to perform under all weather conditions, Philips-Advance's family of signPRO magnetic ballasts offers sign suppliers, manufacturers, and installers a broad range of dependable lighting solutions.

Product data

• General Characteristics

| | |
|--------------------------------|------------------------|
| Lamp Type | T12/HO |
| Number of Lamps | 2-4 piece |
| Input Voltage | 120 V |
| Input Current (Operating) | 4 A |
| Line Frequency | 60 Hz |
| Lamp Footage(for sign ballast) | 20 - 40 FT |
| Ballast Type | Magnetic Fluorescent |
| Base Model | ASB204024BLTP |
| Housing | BL3 |
| Housing Dimensions | 19.19" x 3.44" x 2.69" |
| Housing Material | Metal |
| Suitable for Outdoor use? | Yes |
| Starting Method | Rapid Start |
| Family Name | SignPRO |

• Operating Characteristics

| | |
|---------------------------|--------|
| Automatic restart | Yes |
| Ignition time | 1 s |
| Input Power Gear | 472 W |
| Ballast factor | 0.8 - |
| Ballast Efficacy Factor | 0.17 - |
| Power Factor | 0.984 |
| Lamp Current Crest Factor | 1.7 - |
| Sound Rating | C |
| Max THD | 25 % |

• Wiring Characteristics

| | |
|------------------|---------------|
| Wire Striplength | 0.50/0.375 mm |
| Lamp Connection | Series |
| Wire Gauge | 18AWG |

| | |
|---------------------------------|----------------|
| Wire Length by Color | See data sheet |
| Wire Type | Solid |
| Allowed Wiring Config(Remote) | Yes |
| Allowed Wiring Config(Tandem) | Yes |
| Allowed Wiring Config(Through) | Yes |
| Max Dist. Ball to Lamp(Remote) | 15' |
| Max Dist. Ball to Lamp(Tandem) | Any = 15' |
| Max Dist. Ball to Lamp(Through) | Any = 15' |

• System Chars on driver level

| | |
|------------------|------|
| Rated Lamp Watts | 110W |
|------------------|------|

• Product Dimensions

| | |
|-----------|----------|
| Length A1 | 19.19 in |
| Length A2 | 18.63 in |
| Width B1 | 3.19 in |
| Height C1 | 2.63 in |

• Approval & Application Chars

| | |
|-------------------|------------------|
| EMC Immunity | FCC Non-Consumer |
| Approbation Marks | UL, CSA, RoHS |
| UL Listed | Yes |
| CSA certificate | Yes |
| CEC Listing | No |
| Circle E logo | No |
| CSA E | No |
| cUL certificate | No |

PHILIPS


| | |
|------------------|-----|
| DOE | No |
| FIDE Certificate | No |
| NOM certificate | No |
| RoHS Compliant | Yes |
| SASO Certificate | No |
| UL Recognized | No |

| | |
|--------------------|---|
| Short product name | SIGN BALLAST (2-4) T12/HO 20-40FT 120V |
| Pieces per Sku | 1 |
| eop_pck_cfg | 1 |
| Skus/Case | 1 |
| Bar code on pack | 781087000106 |
| Bar code on case | 30781087000107 |
| Logistics code(s) | 913700586409 |
| eop_net_weight_pp | 9.013 kg |

• Product Data


| | |
|-------------------|---|
| Product number | ASB204024BLTPI |
| Full product name | SIGN BALLAST (2-4) T12/HO 20-40FT 120V |

Dimensional drawing



SIGNPRO MAG SIGN BALLAST (2-4) T12/HO 20-40FT 120V

| Product | A1 (Norm) | A2 (Norm) | B1 (Norm) | C1 (Norm) | D1 (Norm) |
|---|-----------|-----------|-----------|-----------|-----------|
| SIGN BALLAST (2-4) T12/HO 20-40FT 120V | 19.19 | 18.63 | 3.19 | 2.63 | - |



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, February 1
data subject to change