

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ASK1K1 (1)-2/0 to (1)-2/0 Power Dist Block Nsi Industries

| Nsi Industries | |
|---|---|
| Catalog Number | ASK1K1 |
| Manufacturer | Nsi Industries |
| Description | Power Distribution Block, 1 Primary Openings, 1 Secondary Openings, #14 to #2/0 Awg Primary Opening Wire Size, #14 to #2/0 Awg Secondary Opening Wire Size, 175 A, 600 V, Clear Acrylic, Maximum Of +90 °C, 2.9 In Overall Length, 1.04 In Overall Width, 2.34 In Overall Height, 0.58 LB |
| Weight per unit | 0.5800 (lbs/each) |
| Product Category | |
| Features | |
| amperage rating | 175 Amps Per Pole |
| Number of Terminals | |
| Voltage Rating | |
| Warranty | |
| Wire Size | (4) 0 (0 4 4 4) (0 (4) (1) (1) (1) 0 (0 4 4 4) (1) (1) (1) (1) |
| Material, Color, and Finish | |
| Color | Black |
| Dimensions and Weight | |
| Size | L=2.90 - H=2.34 - W=1.04 |
| Descriptions | |
| Description | (1)-2/0 TO (1)-2/0 POWER DIST BLOCK |
| extra long description | NSI AS-K1-K1 Pwr Dist 1x2/0-14Line |
| Features | Power Distribution Block (1) 2/0-14 AWG Primary (1) 2/0-14 AWG Secondary Power Distribution Blocks are made of high strength, high-conductivity aluminum alloy and are mounted in a high-strength glass-filled polyester base. Each block can stand alone or combine with other blocks to form a multi-block set. |
| Special Features | (1) 2/0-14 AWG (Line Side) - (1) 2/0-14 AWG (Load Side) - 175 Amps Per Pole |
| Manufacturer Information | |
| GTIN | 00662381166043 |
| UPC | 662381166043 |
| Taxonomies, Classifications, and Category Description | TEDMINIAL DI OCKE DOMED DICT DI OCKE |
| Type | 0.11. //0.1 |
| | |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | | |
|-----------------|------|--|
| Carton | 1 | |
| Package | 3 | |
| Weight Per each | 0.58 | |

Uses, Certifications, and Standards

| Application | NSI |
|-------------|----------------------|
| Mounting | 2 Mounting Holes |
| standard | Recognized to UL1059 |