



Shown actual size: Ariadni® preset dimmer and 1-gang Fassada® wallplate in white (WH)

### available models

#### source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- fluorescent lighting
- LED lighting
- quiet 3-speed fan controls
- quiet 3-speed fan/light controls

#### control locations

- single pole (one location)
- 3-way (two locations)

### available colors (see page 12 for color swatches)

#### colors (gloss finish)

- |                  |                        |
|------------------|------------------------|
| <b>WH</b> white  | <b>LA</b> light almond |
| <b>IV</b> ivory  | <b>BR</b> brown        |
| <b>AL</b> almond | <b>BL</b> black        |

## Ariadni® dimmers

### product family features

- matches existing switches
- toggle-style switch returns light to suit any activity
- slide adjusts light to your favorite level
- coordinating Fassada® wallplates available separately (including matte, gloss, and stainless steel finishes)
- **eco-dim**® model available

Questions on installation or selection?  
Call Lutron® 24 hours/7 days a week at  
1.800.523.9466 or visit [www.lutron.com](http://www.lutron.com)

**dimmers**



- toggle turns on/off
- slide up to brighten, down to dim
- eco-dim® model guarantees at least 15% energy savings compared to a standard switch

**incandescent/halogen**

single pole	600W	<b>AY-600P-</b>
single pole	1000W	<b>AY-10P-</b>
3-way	600W	<b>AY-603P-</b>
3-way	1000W	<b>AY-103P-</b>

**incandescent/halogen — eco-dim®†** NEW

single pole/3-way	600W	<b>AY-603PG-</b>
-------------------	------	------------------

**magnetic low-voltage**

single pole	600 VA (450 W)	<b>AYLV-600P-</b>
3-way	600 VA (450 W)	<b>AYLV-603P-</b>

Suggested maximum lighting load for magnetic low-voltage dimming is 450W for 600VA products to allow for transformer losses.

† available in white, ivory, almond, and light almond

**dimmers with locator light**



- toggle turns on/off
- slide up to brighten, down to dim
- includes locator light
- not available in black

**incandescent/halogen**

single pole	600W	<b>AY-600PNL-</b>
single pole	1000W	<b>AY-10PNL-</b>
3-way	600W	<b>AY-603PNL-</b>
3-way	1000W	<b>AY-103PNL-</b>

**See page 95 for available colors.**

To order, add color suffix to model number.  
Example: **AY-600P- WH**

**fluorescent dimming** with Hi-lume®, Compact SE™, Eco-10®, EcoSystem® ballasts, and **Hi-lume® LED**



- use with Lutron® 3-wire line-voltage control electronic dimming ballasts
- please refer to the Lutron® Fluorescent Dimming Systems Selection Guide (P/N 366-002) for more information
- no derating if ganged

**fluorescent\***

single pole/3-way 120V	8A	<b>AYF-103P-</b>	
single pole/3-way 277V	6A	<b>AYF-103P-277-</b>	

**LED** with Hi-lume® LED driver only\* NEW

single pole/3-way 120V	8A	<b>AYF-103P-</b>	
single pole/3-way 277V	6A	<b>AYF-103P-277-</b>	

**LED** with GRX-TVI (0-10 VDC sink control)\* NEW

single pole/	16A load	<b>AYF-103P-</b>	
3-way	30 mA control		
	120/277V		

\* requires neutral wire connection

**See page 95 for available colors.**  
To order, add color suffix to model number.  
Example: **AY-103P- WH**

fan control



- toggle turns on/off
- slide up to increase speed, down to decrease
- 3 quiet fan speeds for increased comfort
- for use with only one ceiling paddle fan

**quiet 3-speed control**

single pole/3-way 1.5A

**AYFSQ-F-**  

fan/light control



**fan control** (left)

- slide up to on/increase fan speed, down to off/decrease fan speed
- 3 quiet fan speeds for increased comfort
- designed to reduce motor hum
- for use with only one ceiling paddle fan

**dimmer** (right)

- toggle turns light on/off
- right slider up to brighten, down to dim

**quiet 3-speed control & dimmer**

single pole fan control 1.5A (left) **AY2-LFSQ-**  

single pole dimmer 300W (right)

**See page 95 for available colors.**

To order, add color suffix to model number.

Example: **AYFSQ-F- WH**



Shown actual size: Ariadni® preset dimmer and 1-gang Fassada® wallplate in white (WH)

### available models

#### source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- fluorescent lighting
- LED lighting
- quiet 3-speed fan controls
- quiet 3-speed fan/light controls

#### control locations

- single pole (one location)
- 3-way (two locations)

### available colors (see page 12 for color swatches)

#### colors (gloss finish)

- |                  |                        |
|------------------|------------------------|
| <b>WH</b> white  | <b>LA</b> light almond |
| <b>IV</b> ivory  | <b>BR</b> brown        |
| <b>AL</b> almond | <b>BL</b> black        |

## Ariadni® dimmers

### product family features

- matches existing switches
- toggle-style switch returns light to suit any activity
- slide adjusts light to your favorite level
- coordinating Fassada® wallplates available separately (including matte, gloss, and stainless steel finishes)
- **eco-dim**® model available

Questions on installation or selection?  
Call Lutron® 24 hours/7 days a week at  
1.800.523.9466 or visit [www.lutron.com](http://www.lutron.com)

**dimmers**



- toggle turns on/off
- slide up to brighten, down to dim
- eco-dim® model guarantees at least 15% energy savings compared to a standard switch

**incandescent/halogen**

single pole	600W	<b>AY-600P-</b>
single pole	1000W	<b>AY-10P-</b>
3-way	600W	<b>AY-603P-</b>
3-way	1000W	<b>AY-103P-</b>

**incandescent/halogen — eco-dim®†** NEW

single pole/3-way	600W	<b>AY-603PG-</b>
-------------------	------	------------------

**magnetic low-voltage**

single pole	600 VA (450 W)	<b>AYLV-600P-</b>
3-way	600 VA (450 W)	<b>AYLV-603P-</b>

Suggested maximum lighting load for magnetic low-voltage dimming is 450W for 600VA products to allow for transformer losses.

† available in white, ivory, almond, and light almond

**dimmers with locator light**



- toggle turns on/off
- slide up to brighten, down to dim
- includes locator light
- not available in black

**incandescent/halogen**

single pole	600W	<b>AY-600PNL-</b>
single pole	1000W	<b>AY-10PNL-</b>
3-way	600W	<b>AY-603PNL-</b>
3-way	1000W	<b>AY-103PNL-</b>

**See page 95 for available colors.**

To order, add color suffix to model number.  
Example: **AY-600P- WH**

**fluorescent dimming** with Hi-lume®, Compact SE™, Eco-10®, EcoSystem® ballasts, and **Hi-lume® LED**



- use with Lutron® 3-wire line-voltage control electronic dimming ballasts
- please refer to the Lutron® Fluorescent Dimming Systems Selection Guide (P/N 366-002) for more information
- no derating if ganged

**fluorescent\***

single pole/3-way 120V	8A	<b>AYF-103P-</b>	
single pole/3-way 277V	6A	<b>AYF-103P-277-</b>	

**LED** with Hi-lume® LED driver only\* **NEW**

single pole/3-way 120V	8A	<b>AYF-103P-</b>	
single pole/3-way 277V	6A	<b>AYF-103P-277-</b>	

**LED** with GRX-TVI (0-10 VDC sink control)\* **NEW**

single pole/	16A load	<b>AYF-103P-</b>	
3-way	30 mA control		
	120/277V		

\* requires neutral wire connection

**See page 95 for available colors.**  
To order, add color suffix to model number.  
Example: **AY-103P- WH**

fan control



- toggle turns on/off
- slide up to increase speed, down to decrease
- 3 quiet fan speeds for increased comfort
- for use with only one ceiling paddle fan

**quiet 3-speed control**

single pole/3-way 1.5A

**AYFSQ-F-**  

fan/light control



**fan control** (left)

- slide up to on/increase fan speed, down to off/decrease fan speed
- 3 quiet fan speeds for increased comfort
- designed to reduce motor hum
- for use with only one ceiling paddle fan

**dimmer** (right)

- toggle turns light on/off
- right slider up to brighten, down to dim

**quiet 3-speed control & dimmer**

single pole fan control 1.5A (left) **AY2-LFSQ-**  

single pole dimmer 300W (right)

**See page 95 for available colors.**

To order, add color suffix to model number.

Example: **AYFSQ-F- WH**