

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# **BC6 2 NPT Iron C Mogul Body** *Crouse-Hinds*

Catalog Number	BC6
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Feraloy Iron Alloy, C Shape, 2"
Weight per unit	7.5 (lbs/each)
Product Category	Bodies & Covers

#### **Features**

dimensions 13.7500 IN X 3.0000 IN X 3.1300 IN

### Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

#### **Dimensions and Weight**

Height	3-1/8	
Hub Size	2 in	
Length	13-3/4	
Width	3	

### **Descriptions**

Description	2 NPT IRON C MOGUL BODY
extra long description	CRS-H BC6 2 NPT IRON C MOGUL BODY
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul conduit body, Feraloy iron alloy, C shape, 2"
Product Type	2 NPT Iron C Mogul Body

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274101101
UPC	782274101101

# Taxonomies, Classifications, and Categories

Category Description	MISC FITTINGS
Туре	Mogul conduit body



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Paci	cagi	ng

Carton	<u>2</u>	
Weight Per each	7.45	

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D