

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BIBD43FX 14-4, 2-Sided Uni-Tap Burndy LLC

Catalog Number	BIBD43FX
Manufacturer	Burndy LLC
Description	Aluminum Unitap, Double Sided Entry, #14-#4 Class B & C, #14-#6 Class G, H, I, K, Dlo, 3 Port
Weight per unit	0.1070 (lbs/each)
Product Category	Large Terminals & Connectors

Features

amperage rating	85	
Conductor Size	14-4 AWG	
Material	Aluminum	

Descriptions

Description	14-4, 2-SIDED UNI-TAP
extra long description	BUR BIBD43FX 14-4 TWO SIDED UNITAP,
Long Description	Aluminum UNITAP, Double Sided Entry, #14-#4 Class B & C ,#14-#6 Class G,H,I,K, DLO, 3 PORT
Product Type	RUN/TAP
Special Features	Features: Clear Plastisol covered AL6061-T6 aluminum body, Saves time, lowers installation costs, eliminates taping, Oxide inhibitor pre-installed, Inhibits moisture and contaminants from entering the contact area

Manufacturer Information

Brand	Burndy LLC
GTIN	00621945438712
Manufacturers Part Number	BIBD43FX
UPC	621945438712

Taxonomies, Classifications, and Categories

Category Description	TERMINAL BLOCK ACESSORIES
Туре	BIBD, Multi-Port

Packaging

Carton	1	
Package	100	
Weight Per each	0.107	

Uses, Certifications, and Standards

Application	Tap connections and in-line splice/reductions are made quickly	
	and easily with the UNITAP™ line of connectors	
standard	UL 486A-486B	
Temperature Rating	-40° C to 135 °C	