

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BLB7 2-1/2" BLB MGL Conduit Body *Crouse-Hinds*

Catalog Number	BLB7
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Feraloy Iron Alloy, LB Shape, 2-1/2"
Weight per unit	13.6 (lbs/each)
Product Category	Bodies & Covers

Features

dimensions 16.9100 IN X 4.2500 IN X 5.0900 IN

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

Dimensions and Weight

Height	5-3/32	
Hub Size	2-1/2 in	
Length	16-29/32	
Width	4-1/4	

Descriptions

Description	2-1/2" BLB MGL CONDUIT BODY
extra long description	CRS-H BLB7 2-1/2 NPT IRON LB MOGUL
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul conduit body, Feraloy iron alloy, LB shape, 2-1/2"
Product Type	2-1/2 NPT Iron LB Mogul Body

Manufacturer Information

Brand	Eaton
GTIN	00782274102801
Manufacturers Part Number	BLB7
UPC	782274102801

Taxonomies, Classifications, and Categories

Category Description	Form 9 condulets, covers & gaskets
Туре	Mogul conduit body



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	13.6
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D