

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Package

Weight Per each

BR125 Type BR BRKR 25A/1 Pole 120/240V 10K Eaton Corp

Catalog Number	DD125
Catalog Number Manufacturer	BR125
	Eaton Corp Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch
Description	Plug-On Circuit Breaker, 25 A, 10 Kaic, Single-Pole, 120/240V, BR, #14-4 Awg Cu/Al, BR, Type BR Loadcenters
Weight per unit	0.3000 (lbs/each)
Product Category	1 Pole Standard Trip Plug-In
Features	
dimensions	3.3000 IN X 1.6000 IN X 3.3000 IN
interrupt rating	10
Poles	1
Voltage Rating	120/240 V
Descriptions	
Description	TYPE BR BRKR 25A/1 POLE 120/240V 10K
extra long description	ETN BR125 Type BR Breaker 25A/1 Pol
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR thermal magnetic circuit breaker, Type BR 1-Inch plug-on circuit breaker, 25 A, 10 kAIC, Single-pole, 120/240V, BR, #14-4 AWG Cu/AI, BR, Type BR Loadcenters
Product Type	Type BR Breaker 25A/1 Pole 120/240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786676362153
Manufacturers Part Number	BR125
UPC	786676362153
Taxonomies, Classifications, and C	Categories
Category Description	Loadcenter Plug In Breakers and Accessories
Туре	Thermal magnetic circuit breakers
Packaging	
Carton	1

10

0.3

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

ses, Certifications, and Standards	
Application	Generation - Renewable Energy - Alternative
	EnergyOtherGeneration - Conventional Energy - Conventional
	EnergyMarine Vessels and Equipment - Marine Vessels and
	Equipment - OtherDatacenters - IT Space: CI and Hyper
	Converged
standard	UL 489. Federal Specifications Classification W-C375