

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



standard

## BR24L125SP 1PH 125A Mlo 2/4 Cir Al Bus Surface Cover Eaton Corp

| Catalog Number                   | BR24L125SP   |
|----------------------------------|--|
| Manufacturer                     | Eaton Corp   |
| Description                      | Main Lug Load Center, 2 Spaces, 4 Circuits, 125 A, 120/240 V Ac, #14 to 1/0 Awg Wire Size, Metallic Material, Aluminum Bus Material, 6.88 In Overall Length, 4.50 In Overall Width, 12 In Overall Height, Surface Mount (Trim)   |
| Weight per unit                  | 5.4 (lbs/each)   |
| Product Category                 | Single Phase Main Lug Load Cen   |
| Features                         |  |
| amperage rating                  | 125  |
| Cover Type                       |  |
| max amps                         | 125  |
| max spaces/poles                 | 2/4  |
| Phase                            | 1  |
| Wattage                          | Four-pole  |
| Dimensions and Weight            |  |
| Depth                            | 3.88   |
| Height                           | 21   |
| Size                             | 6  |
| Width                            | 14.31  |
| Descriptions                     |  |
| Description                      | 1PH 125A MLO 2/4 CIR AL BUS SURFACE COVER  |
| extra long description           | ETN BR24L125SP 1Ph/BR LC 125A MLO 2  |
| Special Features                 | Current design   |
| Manufacturer Information         |  |
| GTIN                             | 00786676002271   |
| UPC                              | 786676002271   |
| Taxonomies, Classifications, and | d Categories   |
| Category Description             | LOADOFNITEDO A COVEDO  |
| Type                             |  |
| Packaging                        | •  |
| Carton                           | 1  |
| Weight Per each                  | 5.4  |
| Uses, Certifications, and Standa |  |
| Mounting                         | C. C. A.   |
| 9                                | and and an arrange of the second of the seco |

UL 50,UL 67