

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BT2MC0 7.9" 18LB BLK Nylon CBL Tie Panduit Corporation

Catalog Number	BT2MC0
Manufacturer	Panduit Corporation
Description	The BT2M-C0 Dome-Top [®] Barb Ty, Features A Unique Patented
	Design With Its Round Smooth Edges. Paired With The
	Stainless-Steel Locking Barb, These Cable Ties Provide Consistent
	Performance, Reliability and Infinite Adjustability Through The Entire Bundle Range. Miniature Cross Section, 7.9" (201MM)
	Length. Appropriate For Indoor/Outdoor Use, Made Of Weather
	Resistant Nylon 6.6 With High Resistance to Ultraviolet Light, Are
	Black In Color and Come In Packages Of 100.
Weight per unit	0.1770 (lbs/each)
• •	y Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	18
Dimensions and W	/eight
Length	7.9
Thickness	0.05
Descriptions	
Description	7.9" 18LB BLK NYLON CBL TIE
•	ption PAN BT2M-C0 Dome-Top® BT2M-C0 Barb
Long Description	
	design with its round smooth edges. Paired with the
	stainless-steel locking barb, these cable ties provide consistent
	performance, reliability and infinite adjustability through the
	entire bundle range. Miniature cross section, 7.9" (201mm)
	length. Appropriate for Indoor/Outdoor use, made of Weather
	Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 100.
Product Type	Dome-Top® BT2M-C0 Barb Tie, Black, Uv PA6.6, 7.9"L, 18LB, PK
Special Features	·
Manufacturer Info	
Brand	Panduit®
GTIN	00074983602865
Manufacturers P	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	Cable Tie
Packaging	
Carton	100
Package	1000
	0.177
Lloss Cartifications and Stand	

Uses, Certifications, and Standards

standard

UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC 10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant