

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BUB3 1" Bub Conduit Body Crouse-Hinds

Catalog Number	BUB3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Feraloy Iron Alloy, Ub Shape, 1"
Weight per unit	2.5 (lbs/each)
Product Category	Bodies & Covers
eatures	
dimensions	9.1900 IN X 2.1900 IN X 2.6900 IN
Naterial, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
	Licetrogalvanized with Aldmindin Aciyile Fainted
Dimensions and Weight	2 11/1/
Height	2-11/16
Hub Size	1 in
Length	9-3/16 2-3/16
Width	2-3/10
Descriptions	
Description	1" BUB CONDUIT BODY
extra long description	CRS-H BUB3 1 NPT IRON UB MOGUL BODY
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul conduit body, Feraloy iron alloy, UB shape, 1"
Product Type	1 NPT Iron Ub Mogul Body
Anufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00700074100000
Manufacturers Part Number	BUB3
UPC	782274108308
axonomies, Classifications, and (
Category Description	
	Mogul conduit body



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Package	2
Weight Per each	2.45

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D