

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



C75CG 3/4" C Threaded Conduit Body W/Cover/Gasket

L.H. Dottie CO.	eaded Collduit Body W/Cover/Gasket
Catalog Number	C75CG
Manufacturer	L.H. Dottie CO.
Description	C Style Conduit Body With Cover and Gasket, 3/4 In. Hub Size, Wall Mounting, Die Cast Copper Free Aluminum Material, Threaded Connection, Neoprene Gasket
Weight per unit	0.4150 (lbs/each)
Product Category	Alum
eatures	
connection	Threaded
Dimensions and Weight Hub Size	3/4
escriptions estimates and the second estimates are second estimates and the second estimates are second estimates and the second estimates and the second estimates are second estimates are second estimates and the second estimates are second estimates are second estimates and estimates are second estimates are seco	
Description	3/4" C THREADED CONDUIT BODY W/COVER/GASKET
extra long description	DOTTIE C75CG 3/4" Threaded Conduit
Long Description	C Style Conduit Body with Cover and Gasket, 3/4 in. hub size, Wall mounting, Die Cast Copper Free Aluminum material, Threaded connection, Neoprene gasket
Product Type	3/4" Threaded Conduit Bodies With Covers and Gaskets
Special Features	The flat back design allows the unit to be mounted close to the wall; They are available as bodies only, or as bodies assembled with covers and gaskets; Threaded conduit Bodies with cover an gasket are used with rigid conduit to provide access to the interior of a conduit system
/lanufacturer Information	
Brand	LH DOTTIE
GTIN	00781002107040
Manufacturers Part Number	C75CG
UPC	781002107040
axonomies, Classifications, and (Categories
Category Description	CAFETY DDODLICTS
Туре	Conduit Bodies with Cover and Gasket
ackaging	
Carton	10
Weight Per each	0.415

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Interior	
Mounting	WALL MOUNT	
standard	UL Listed	